1	UNITED STATES BANKRUPTCY COURT FOR THE WESTERN DISTRICT OF NORTH CAROLINA	
2	CHARLOTTE DIVISION	
3		
4	IN RE:	
5	GARLOCK SEALING TECHNOLOGIES ) LLC, et al, ) No. 10-BK-31607	
6	Debtors. ) VOLUME VI-A	
7		
8		
9	TRANSCRIPT OF ESTIMATION TRIAL BEFORE THE HONORABLE GEORGE R. HODGES	
LO	UNITED STATES BANKRUPTCY JUDGE JULY 29, 2013	
L1	APPEARANCES:	
L2	On Behalf of Debtors:	
L3	GARLAND S. CASSADA, ESQ.	
L4	Robinson Bradshaw & Hinson, PA 101 North Tryon Street, Suite 1900 Charlotte, North Carolina 28246	
L5	JONATHAN C. KRISKO, ESQ.	
L6	Robinson Bradshaw & Hinson PA 101 North Tryon Street, Suite 1900	
L7	Charlotte, North Carolina 28246	
L8	LOUIS ADAM BLEDSOE, III, ESQ. Robinson Bradshaw & Hinson PA	
L9	101 North Tryon Street, Suite 1900 Charlotte, North Carolina 28246	
20	RICHARD C. WORF, ESQ.	
21	Robinson Bradshaw & Hinson, PA 101 North Tryon Street, Suite 1900	
22	Charlotte, North Carolina 28246	
23		
24		
25		

1 APPEARANCES (Continued): 2 On Behalf of the Debtors: 3 RAY HARRIS, ESQ. Schachter Harris, LLP 4 400 East Las Colinas Blvd. Irving, Texas 75039 5 CARY SCHACHTER, ESQ. 6 Schachter Harris, LLP 400 East Las Colinas Blvd. 7 Irving, Texas 75039 8 C. RICHARD RAYBURN, JR., ESQ. Rayburn Cooper & Durham, PA 9 227 West Trade Street, Suite 1200 Charlotte, North Carolina 28202 10 SHELLEY KOON ABEL, ESQ. Rayburn Cooper & Durham, PA 11 227 West Trade Street, Suite 1200 12 Charlotte, North Carolina 28202 13 ALBERT F. DURHAM, ESQ. Rayburn Cooper & Durham, PA 14 227 West Trade Street, Suite 1200 Charlotte, North Carolina 28202 15 ROSS ROBERT FULTON, ESQ. 16 Rayburn Cooper & Durham, PA 227 West Trade Street, Suite 1200 17 Charlotte, North Carolina 28202 18 JOHN R. MILLER, JR., ESQ. Rayburn Cooper & Durham, PA 19 227 West Trade Street, Suite 1200 Charlotte, North Carolina 28202 20 ASHLEY K. NEAL, ESQ. 21 Rayburn Cooper & Durham, PA 227 West Trade Street, Suite 1200 2.2 Charlotte, North Carolina 28202 23 WILLIAM SAMUEL SMOAK, JR., ESQ. Rayburn Cooper & Durham, PA 24 227 West Trade Street, Suite 1200 Charlotte, North Carolina 28202

1	APPEARANCES (Continued.):
2	On Behalf of Interested Parties:
3	Carson Protwall LP:
4	JULIE BARKER PAPE, ESQ. Womble Carlyle Sandridge & Rice, PLLC
5	P.O. Drawer 84 Winston-Salem, North Carolina 27102
6	Coltec Industries Inc.:
7	DANIEL GRAY CLODFELTER, ESQ.
8	Moore & Van Allen, PLLC 100 North Tryon Street, Suite 4700
9	Charlotte, North Carolina 28202-4003
10	HILLARY B. CRABTREE, ESQ. Moore & Van Allen, PLLC
11	100 North Tryon Street, Suite 4700 Charlotte, North Carolina 28202-4003
12	MARK A. NEBRIG, ESQ.
13 14	Moore & Van Allen, PLLC 100 North Tryon Street, Suite 4700 Charlotte, North Carolina 28202-4003
15	EDWARD TAYLOR STUKES, ESQ.
16	Moore & Van Allen, PLLC 100 North Tryon Street, Suite 4700
17	Charlotte, North Carolina 28202-4003
18	Creditor Committees:
19	Official Committee of Asbestos Personal Injury Claimants:
20	LESLIE M. KELLEHER, ESQ. Caplin & Drysdale, Chartered
21	One Thomas Circle NW, Suite 1100 Washington, DC 20005
22	JEANNA RICKARDS KOSKI, ESQ.
23	Caplin & Drysdale, Chartered One Thomas Circle NW, Suite 1100 Washington, DC 20005
24	

1 APPEARANCES (Continued.): 2 Official Committee of Asbestos Personal Injury Claimaints: 3 JEFFREY A. LIESEMER, ESQ. Caplin & Drysdale, Chartered 4 One Thomas Circle NW, Suite 1100 Washington, DC 20005 5 KEVIN C. MACLAY, ESQ. 6 Caplin & Drysdale, Chartered One Thomas Circle NW, Suite 1100 7 Washington, DC 20005 8 TODD E. PHILLIPS, ESQ. Caplin & Drysdale, Chartered 9 One Thomas Circle NW, Suite 1100 Washington, DC 20005 10 TREVOR W. SWETT, ESQ. Caplin & Drysdale, Chartered 11 One Thomas Circle NW, Suite 1100 12 Washington, DC 20005 13 JAMES P. WEHNER, ESQ. Caplin & Drysdale, Chartered 14 One Thomas Circle NW, Suite 1100 Washington, DC 20005 15 ELIHU INSELBUCH, ESQ. 16 Caplin & Drysdale, Chartered 600 Lexington Avenue, 21st Floor 17 New York, New York 10022 18 NATHAN D. FINCH, ESQ. Motley Rice, LLC 19 1000 Potomac Street, NW, Suite 150 Washington, DC 20007 20 GLENN C. THOMPSON, ESQ. 21 Hamilton Stephens Steele & Martin 201 South College Street, Suite 2020 2.2 Charlotte, North Carolina 28244-2020 23 TRAVIS W. MOON, ESQ. Moon Wright & Houston, PLLC 24 227 West Trade Street, Suite 1800 Charlotte, North Carolina 28202

1	APPEARANCES (Continued.):
2	Official Committee of Asbestos Personal Injury Claimaints:
3	RICHARD S. WRIGHT, ESQ. Moon Wright & Houston, PLLC
4	226 West Trade Street, Suite 1800 Charlotte, North Carolina 28202
5	ANDREW T. HOUSTON, ESQ.
6	Moon Wright & Houston, PLLC
7	227 West Trade Street, Suite 1800 Charlotte, North Carolina 28202
8	SCOTT L. FROST, ESQ. Waters Kraus, LLP
9	222 North Sepulveda Boulevard, Suite 1900 El Segundo, California 90245
10	JONATHAN A. GEORGE, ESQ.
11	Waters Kraus, LLP 3219 McKinney Avenue
12	Dallas, Texas 75204
13	Future Asbestos Claimaints:
14	KATHLEEN A. ORR, ESQ.
15 1152 15th S	Orrick, Herrington & Sutcliffe, LLP 1152 15th Street, N.W., Columbia Center Washington, DC 20005-1706
16	JONATHAN P. GUY, ESQ.
17	Orrick, Herrington & Sutcliffe, LLP 1152 15th Street, N.W., Columbia Center
18	Washington, DC 20005-1706
19	Official Committee of Unsecured Creditors:
20	DEBORAH L. FLETCHER, ESQ.
21	FSB Fisher Broyles, LLP 6000 Fairview Road, Suite 1200 Charlotte, North Carolina 28210
22	Charlotte, North Carollia 20210
23	
24	
25	

1 PROCEEDINGS 2 JULY 29, 2013, COURT CALLED TO ORDER 9:30 A.M.: 3 MORNING SESSION: 4 THE COURT: Good morning. ALL COUNSEL: Good morning, Your Honor. 5 6 THE COURT: Okay. We're going to shift gears to 7 Mr. Frost; is that right? 8 MR. FROST: Good morning, Your Honor. We call 9 Dr. William Longo. 10 THE COURT: Okay. 11 WILLIAM LONGO, 12 Being first duly sworn, was examined and testified as follows: 13 DIRECT EXAMINATION BY MR. FROST: 14 15 Good morning, Dr. Longo. Could you please state and spell your name for the record? 16 17 Α. William Edward Longo. L-O-N-G-O. And Dr. Longo, where are you from? 18 Q. 19 Α. I live in Cumming, Georgia, which is just right outside 20 of Atlanta, Georgia. 21 And what field do you have your Ph.D in? Ο. A. In material science and engineering. 2.2 23 Q. And what is material sciences? 24 A. Material science and engineering is literally the study 25 of materials. These materials are usually broken down into

four groups; metallurgy or metals. I'm sorry. Ceramics, metallurgy or metals, ceramics or minerals. Minerals such as asbestos. Plastic or polymers. And my specialty in graduate school was bio materials. And these would be materials that were implanted into the human body.

- Q. And can you briefly describe your educational background?
- A. Yes, sir. I received a Bachelor of Science in microbiology. I went on to graduate school in material science and engineering. I received a Masters of Science in material science and engineering. And then finally in 1983 I received my Ph.D or Doctorate in material science and
- Q. Now, you worked for a company called MAS. What is MAS?

engineering, all at the University of Florida.

A. MAS stands for Materials Analytical Services. Everybody
just calls it MAS to make it easy. What MAS is, is a
laboratory consulting group and testing facility.

So we have a wide range of services we provide to industry consultants, universities, the government, that sort of thing.

Q. Now I have a slide up on the board that sort of describes some of the areas. You're not an individual like some folks we've seen who are basically mom-and-pop consulting. They've been in the industry before, and then they get out and sort of do consulting.

Is your laboratory an ongoing lab that conducts analysis

Laura Andersen, RMR 704-350-7493

for various people and different types of things?

- A. Yes, sir. The facility -- the laboratory is located in Suwanee, Georgia which is right next to Cumming. And it's a 20,000-square foot facility. We have -- I think the current count is 35 employees. They range in a number of different disciplines, that provide services to clients all over the
- disciplines, that provide services to clients all over the country, and literally all over the world.
- Q. Now, we have up on the board, "mold". What types of things have you done with mold cases or mold counts?

A. Mostly what we do with mold is just analysis. Where somebody has a suspected mold problem in a building, usually, either from water intrusion or some other factor that has caused mold to start growing.

We take samples and analyze them and tell you if it is mold or not. They take air samples and tell you how many mold spores per cubic centimeter of air, or per cubic meter of air that's in the air to meet certain standards. So it's both identification, the quantification, and we're certified to do the work.

- Q. In these types of certifications, how are you certified? How is your laboratory certified?
- A. We're certified by a couple different agencies. As you see on the bottom there, the first one is the American Industrial Hygiene Association. They have certified our laboratory to do a wide array of testing, including mold spore

counting and analysis, asbestos for the different types of protocols, organic analysis, air analysis, what have you.

The second one that we've been certified for some time is the National Voluntary Laboratory Accreditation Program, which essentially is run by -- it's an offshoot of the Environmental Protection Agency which certifies us for doing both air and bulk analysis or asbestos.

A2LA is another certification body that comes in and provides our ISO certification.

So we spend a lot of time making sure we have the certifications for the types of analysis we do.

- Q. And it has up there lead testing/metals. What types of things have you done in the past with those?
- A. Well, again, as a laboratory and again we're certified for doing that analysis, people who -- consultants, industry, lead testing in products that have been manufactured typically from other countries that have high contents of lead.

Lead paint was a common paint material that was used in all kinds of homes, industries, back in the year. So folks who want to understand how much lead may be potentially in the paint, does it contain lead, a lot of public buildings. So they send samples in, and we can analyze the paint chips, white samples, air samples, in how much lead is there, and does that exceed the recommendations or the regulations for what is allowable.

Q. And you have CPSC toy testing. Was that also part of that lead issue?

- A. Correct. Typically toys, especially coming from other countries, being sold in this country, tend to use the wrong types of ingredients at times. And so we can certify that particular batch of toys coming in from a manufacturer meets the -- doesn't have leads, plus other types of organics not allowed. We do quite a bit of that.
  - Q. We will spend a lot of time talking about asbestos. But what has your laboratory done -- what types of people has it worked for outside of the asbestos arena? Who are your clients that you're doing this type of testing for, any of the testing that we're -- that -- the different types that's not asbestos related?
  - A. In our semiconductor work we have worked for the likes of IBM/Intel. In the federal government we have worked for the GSA, Governmental Services Administration. We've worked for the Environmental Protection Agency. We have worked for the FAA.

We have worked for a wide range of manufacturers, carpet manufacturers from around the world, furniture manufacturers from around the world, testing their products to see if they meet organic emissions standards, commonly known as VOC, volatile organic compounds. An example of that would be the new car smell. Which has kind of a pleasant sweet odor. That

new car smell is actually volatile organic compounds emitting from the materials inside the car. It's not really that good for you, even though it smells good.

So there's all kinds of standards now for different types of products for those emissions, and we certify the products that they can meet these certain activities.

Every carpet manufacturer in Georgia, which has a lot, has used our services. A large number of different manufacturers of office furniture used our services for this testing. We have quite a few clients.

- Q. Now you mentioned the AIHA that certifies your laboratory. Have you been familiar with some of the statements the AIHA made concerning asbestos in the past?
- 14 | A. I have.

- Q. And we talked to Mr. Boelter about this AIHA Job, Health, and Safety on the care of Asbestos-Containing Flooring Materials. Is this something you reviewed in the past?
- A. I have.
- Q. Is this something that you agree with when they talk about asbestos being a known human carcinogen and there being no safe threshold of exposure for asbestos?
- MR. HARRIS: Objection, Your Honor. This is outside his area of expertise to speak about health issues and the health effects of asbestos. I think they'll probably agree with that.

1 THE COURT: Sustained.

BY MR. FROST:

2

3

4

5

6

11

12

13

23

24

25

- Q. Dr. Longo, have you done extensive work concerning asbestos and as a microscopist and material scientist, do you have to be aware of whether asbestos is a danger to human health?
- 7 A. Yes, sir. I typically don't testify about it. But
  8 certainly we're aware of it, because of the precautions we
  9 take inside our laboratory to make sure individuals aren't
  10 exposed to asbestos fibers.
  - Q. And are you aware of the AIHA's position on whether asbestos is a known human carcinogen, the organization that certifies your laboratory?
- 14 | A. Yes, sir, I've seen this statement before.
- Q. Now, have you -- other than dealing with all these other issues, have you also developed a specialty in asbestos?
- 17 A. Yes, sir, I have.
- 18 Q. And how did you develop that specialty?
- A. Goes back many years. When I was in graduate school one of the areas that I used -- one of the techniques I used a lot of to get my Ph.D was both scanning electron microscopy, transmission electron microscopy.
  - So in the early '80s it occurred to me that the issue with asbestos, that electron microscopy is the best technique for making measurements and air samples versus optical

microscopy. So in the '80s I got involved in using electron microscopes to measure asbestos.

Over time that has -- the types of samples and the number of people have worked for me increased. So if I were to estimate how many samples we have analyzed to date involving asbestos in our laboratory, I would say we easily exceed 400,000 individual asbestos samples of every type that have been sent to us from literally around the world.

- Q. And I guess that's a good point. Are samples sent to your laboratory just in the context of litigation?
- A. No, sir, they're not.

- Q. What -- how do individuals send samples to MAS and what type of individuals outside of litigation send asbestos samples to be tested by MAS?
  - A. Typically they're engineering consulting, environmental engineering firms that have been hired to go and survey buildings. And in these buildings that have been built up to '72, '73 for fireproofing and acoustical plasters, typically contain asbestos. And buildings owners of all types want surveys done to see what their asbestos issue is.

So these engineering firms and consultants send them to us just for an analysis that tell them in those samples how much asbestos is present, if any. And if it is present, what type.

Q. Now besides yourself being a Ph.D in material science, do

- 1 you also have industrial hygienists and those type people
  2 working for your firm?
- 3 A. I do.

6

7

8

9

10

11

20

21

- 4 Q. How many industrial hygienists do you have working for you?
  - A. Currently we have three industrial hygienists that are on staff.
  - Q. Now -- and we're going to talk in depth a little bit more about the different microscopy techniques. But have you published in the peer-review literature concerning the types and techniques you and I will talk about?
- 12 A. Yes, sir.
- 13 Q. When was that published and what was published?
- A. I believe this was published -- this was published in
  January of 2002 in the "Applied Occupational Environmental
  Hygiene Journal".
- And what was published was essentially our work practice simulations involving the removal of gaskets from flanges, pipe flanges and valve flanges.
  - Q. Now have you also been asked to speak about asbestos issues in front of different groups?
- 22 A. Yes, sir, I have.
- 23 Q. What groups have you spoke in front of?
- A. The American Industrial Hygiene Association, the continuing education courses at both Georgia Tech and the

University of New York.

2.2

I have also been asked to speak in front of both plaintiff's attorneys at one of their conferences, as well as defense attorneys at their conference on our work.

Mostly speaking engagements I've had in the past involve things like meetings of industrial hygiene -- or the -- you know, the National Asbestos Council.

I've even been asked to provide -- speak to the Pittsburgh Corning Trust about air levels and concentrations involved in asbestos. So really a wide range of folks.

- Q. And have you been involved in previous bankruptcy proceedings?
- 13 A. Yes, sir, I have.
- Q. What previous bankruptcy proceedings have you been involved in?
  - A. I was involved in the Celotex bankruptcy proceeding in Tampa, many years ago.
  - Q. You mentioned the PC trust, you also at least gave a presentation to the trust itself after the bankruptcy?
  - A. After the bankruptcy the -- one of the trustees saw one of my presentations about measurement, dust levels associated with the product of issue. They wanted me to come in and talk to the employees that were involved in the trust. Essentially provide them what we have found and shown.

And they were particularly interested in looking at the Laura Andersen, RMR 704-350-7493

- high intensity lighting, demonstrating how visible dust versus
  dust seen under high intensity.
- Q. That's the Tyndall lighting that we'll talk about in a minute?
  - A. Yes.

5

9

10

11

12

13

14

15

16

17

18

25

- Q. Now, other than your work at Georgia Tech and the University of New York, have you taught other courses on asbestos over the years?
  - A. Yes, sir. I have taught courses at the American

    Industrial Hygiene Association meeting in which I came in as a speaker in one of their continuing education courses for one hour.

Also I have put on an eight-hour course for the use of transmission electron microscopy and helping industrial hygienists, certified industrial hygienists, as well as industrial hygienists, to help solve measurement problems.

- Q. Have you done work on behalf of the federal government in the past?
- 19 A. Yes, sir, I have.
- 20 | Q. What have you done for the federal government?
- A. We have ongoing work involving the clean-up of WR Grace vermiculite sites around the country that are superfund clean-up sites in which WR Grace had many facilities around the country where they exfoliated their vermiculite.
  - Exfoliation just means taking raw vermiculite, heating it

to very high temperatures, causes the air to expand in the mineral and makes it fluffy, like popcorn. When they did this, they contaminated the surrounding areas.

So, we have ongoing projects in helping develop, both analysis, as well as doing analysis, for air samples, soil samples, and what have you.

We were asked by the EPA through their contractor at one point to help develop a new testing method for analyzing asbestos in soil, because of the problem of all the nonasbestos sand and dirt materials interfering with the analysis. So we did that work.

- Q. So the EPA at that time prior to asking you, did not have a protocol for trying to find out if asbestos was contained within soil. And what you all did was, you helped them try to come up with a protocol or procedure to find out how much asbestos could be in contaminating soil?
- A. Not quite.

- 18 Q. Okay. What exactly did you do?
  - A. Well, the EPA had a protocol for bulk analysis. Where you take a bulk sample of any type, analyze it by polarized light microscopy. And by using polarized light microscopy, and stereo optical microscopy, the person doing the analysis, the microscopist, can make an estimate of the amount of asbestos present, if it is present. So you can get a volume percent, tell the type, and that's been standard protocol for

years and years.

2.2

What EPA was interested in was how to enhance that, because of the interfering factors associated with soil. You're not dealing with a product where somebody has put 10 or 15 or 20 or 80 percent asbestos in the material, and you're taking a piece of that material and analyzing it.

You're dealing with contamination that has been mixed in with the dirt, so it's not really a product. So you have all these interfering materials. So they were looking for a better method to test for that. So it's not really they didn't have a method, they needed a better method.

- Q. When the EPA needed a better method, you're one of the folks that came to to try to help them with that issue?
- 14 A. Through their contractor, yes, sir.
- 15 Q. Now have you also been involved in any EPA peer-reviews?
- 16 A. Yes, sir, I have.
- Q. What has been your involvement in that, what are the issues?
  - A. Two types of issues. One for a few years, I was invited, myself along with a couple other scientists, every six months to go to EPA in Cincinnati and look over their research. We would peer-review what they were doing with asbestos issues in buildings, then make recommendations for new testing, or new areas. Or if they had analysis or study done, we would peer-review the analysis.

The other area I was involved in was myself and a number of microscopists were invited to EPA to help them develop a testing protocol for measuring asbestos and dust. We spent two days there debating on what was the best method. And the EPA ultimately chose the method that myself and Mr. Hatfield worked on. They never published it. It was just a draft method. But we did do that work for them.

- Q. And so when the EPA yet again was trying to deal with issues of asbestos and dust, that's something that you've been involved with intimately with the EPA to help them try to develop protocols?
- 12 A. Correct.

2.2

- Q. Now what's the EIA. I think it used to be called the National Asbestos Council.
- 15 A. That's correct.
- 16 Q. What work have you done with them?
  - A. Well EIA was a membership organization. So when it was the National Asbestos Council, before it became the EIA, they formed committees that were interested in helping to develop and refine some of the testing protocols that were being used at the time for transmission of electron microscopy. So I was involved with that organization.

I joined the committee, I was elected as the vice chairman of that particular committee, and ultimately became the chairman of the committee for the electron microscopy

group, working with the protocols at the time, and working along the lines to improving them.

- Q. And I have the National Institute of Building Sciences.
- 4 Who is that, and what's been your involvement with them?

- A. Our laboratory's been involved with that area, especially with the testing of products going into the buildings. So the group and my lab sit on the committees of these various organizations to help develop protocols.
  - Q. Now, you have been involved with asbestos litigation.

    How did you become involved in asbestos litigation?
  - A. Again, so long I almost forgot the first time.

But the first case I got involved in was looking at the issue of dust analysis in buildings, to see if in-place asbestos materials became dusted over time in contaminated building surfaces.

Since our laboratory had spent a lot of time developing that method, we were asked to do testing and testify about it.

Ultimately very early on I was also asked as a material scientist if we could figure out how to identify in-place products. Such as a building that has fireproofing in it, asbestos-containing fireproofing. Can you take a sample of that, analyze it and determine who made it.

The manufacturers of asbestos products for buildings all had formulas for what they put in their product. Once we obtained those, and be fair, through the courts, we were able

to determine that each product of fireproofing acoustical plaster, actually had its own fingerprint, had its own specific ingredient or set of ingredients that no other material had, called it product identification.

- Q. Now Dr. Longo, this product identification of these products that are in place, would a person who is just looking at those products, say it's ceiling tile, floor tile, or thermal insulation, would they have any ability if it's just sitting there in place to know who manufactured those products?
- A. Probably not. Occasionally on thermal insulation, if it has a canvas covering on it. Some manufacturers would have printed their name on it. But you don't see that too often.

But fireproofing, acoustical plaster, ceiling tiles -- ceiling tiles sometimes on the back of the tile, but that's also rare.

So what we did, not so much for thermal insulation products, but fireproofing acoustical plasters and ceiling tiles, we developed the ability to analyze those materials and then tell you who made it. Sometimes we can tell you even the range of years it was made, because a lot of manufacturers made slight changes to the product while it has asbestos in it.

Q. Now, let's talk about thermal insulation just briefly. If a piece of thermal insulation is in place and it's been

covered by either a pad or some type of wrapping, if an individual who's a worker is just looking at that thermal insulation as it sits there in place, is there any way for him to know whether it contains asbestos or not, or the brand of

those products, just looking at it?

A. You're not going to be able to know the brand. It depends on how much knowledge the worker had. If the worker had knowledge about when the material was put in, and had knowledge that these materials had asbestos in it during particular times, then maybe. But a lot of times no.

Unless you do an analysis, or you have additional information, the age, that sort of thing, you wouldn't be able to.

- Q. And isn't that one of the things that happens throughout, like, say a refinery. You treat everything as if it contains asbestos, but you really have to do that bulk sampling to verify whether it does or doesn't?
- A. Yes, sir, they always do. Anytime any facility, especially today, wants to know where asbestos is and where there is not asbestos, they would do sampling.
- Q. Now Dr. Longo, have you -- this bulk sampling of materials, have you also done other types of testing in litigation for asbestos?
- 24 A. I have.

25 Q. And who have you done that for?

A. Which part, I'm sorry?

1

8

9

10

11

12

13

14

15

16

2.2

Α.

- Q. The -- well, I guess the bulk sampling. Who did you do that for, then we'll go through the regular testing.
- A. In the litigation context, when we're doing bulk sampling, it's usually our own research where we're doing the study, or we've been hired by attorneys to analyze materials to see if they have asbestos on them or not.

For the attorneys, most of the work we've done in their behalf has been for plaintiff's attorneys. But we also have defendant's attorneys, as well as the company send us materials when they want to know if they have asbestos in them or not. To see -- because sometimes their records are not as good as they ought to be, I guess, from all those years back and they can't quite tell.

- Q. So -- and the last time I saw you professionally, do you remember that?
- 17 A. I do, it was a long day.
- 18 | Q. Who were you testifying for?

Yes, sir, they were.

- 19 A. I was testifying on behalf of Scott's Fertilizer.
- 20 Q. Was Scott's Fertilizer a defendant in that particular 21 case, it was a Waters and Kraus case?
- Q. Was I taking your deposition as the plaintiff's lawyer on
- 24 the other side?
- 25 A. Yes, sir, for I believe almost five hours.

Q. Maybe a little shorter than Mr. Harris. Thank you.

Other than the Scott's company, have you testified and

been retained by defendants in asbestos litigation, not just

plaintiffs?

A. Yes, sir, I have.

- Q. And just generally what types of companies have you either been retained for or testified for?
- A. Well, we have Scott's Fertilizer that I worked for, have testified in deposition for, I think, now on two or three occasions.

We work for some of the safety apparel companies, asbestos gloves, both Guard-Line and Steel Grip. I've testified in court for Guard-Line in Mississippi. We work for Bondo that made body filler. We work for the American Insulated Wire Company, which made asbestos wire. We have worked for General Electric where we have done testing on a couple products.

A hair dryer that had asbestos materials inside the hair dryer to insulate the heater coils where the air blows over, some of their appliance wire.

We have been retained by -- from Westinghouse. We have been retained by Abex, which was -- sold asbestos-containing brake shoes. We have been retained and done work for Lincoln Electric which sold asbestos-containing welding rods.

We used to work for IMO which was a pump manufacturer.

- We have looked at -- I know there's a couple more, but that's what --
- 3 Q. And so the things that you and I are going to talk about
- 4 here in a few minutes about the gasket studies and studies of
- 5 asbestos-containing materials, you've done those type of
- 6 studies on behalf of individuals bringing lawsuits and also on
- 7 | behalf of defendants in asbestos litigation?
- 8 A. Yes, sir. But to be fair, most of my work is on behalf
- 9 of plaintiffs.
- 10 Q. And what's your hourly rate?
- 11 A. \$450.
- 12 Q. Dr. Longo, are you aware of how much money MAS has billed
- 13 in this particular case?
- 14 A. There's two of us working on this case, myself and
- 15 Mr. John Templin who is a CIH. I haven't looked at the very
- 16 | last bills, but I would estimate somewhere between 160- and
- 17 | \$170,000 for both of us.
- 18 | Q. Nothing close to a million dollars?
- 19 A. No, sir.
- 20 Q. Now we talked a little bit about the EPA has the -- has
- 21 | MAS and you, yourself, have you been involved with any
- 22 protocols?
- 23 A. Yes, sir.
- 24 | Q. And what are protocols and what have you been involved
- 25 | with?

A. A protocol is a testing procedure. Think of it as a recipe. And the recipe starts at A and goes to Z.

A protocol is where -- it's the ability to show you how to do an analysis, where you go from step one to step two, step three. And the EPA was interested in developing protocols that I've mentioned before, about a better way to test for asbestos soil contamination, from these vermiculite exfoliation superfund sites which had to deal primarily with amphiboles, tremolite.

And also the dust analysis that we talked about, in which they were interested in having a technique to understand how asbestos in place in a building, is it causing contamination on the surfaces in that building over time, because building vibration, et cetera.

- Q. Now, is that -- what's this concept of re-entrainment when we talk about asbestos?
- A. Re-entrain is literally asbestos debris and dust that have typically got on a worktable or floor, and -- after the use of asbestos product. Then somebody's asked to come clean it up.

And this clean up -- can be a lot of times compressed air, which is not allowed to be used anymore, to dry sweeping with a broom or foxtail brush, just to get up the dust and debris.

That activity will re-entrain or re-suspend the dust that Laura Andersen, RMR 704-350-7493

is on the surface of the table. So if you use an asbestos product on a worktable, you're going to see over time that there is dust buildup on that table.

If you go back and clean that table up, you're going to have that dust be re-entrained, since it has asbestos in it, it will of course cause an additional exposure to whoever is doing that work, or bystanders happen to be around the work.

- Q. So when you're looking at exposures to asbestos, you're not just dealing with the individual who is doing the work itself, it's people doing cleanup. Say, for example, an individual has opened up a valve and has old packing and they pulled that out and blow it with an air hose, that's a type of exposure somebody would have directly, correct?
- A. Correct.

- Q. And then what you're dealing with is once that asbestos is settled, somebody cleaning up later?
- 17 A. Correct.
  - Q. How long does it take for somebody who takes a valve and they've taken out the old packing and they blow it out with an air hose. How long does that asbestos stay up in the air?
  - A. Well, it depends. It's not all going to stay up in the air -- let me back up.

You know, there was a theoretical study once about how long it would take a five micrometer fiber in still air, dropped at a height of 6 feet, to touch the floor. I think

they calculated eight hours.

Q. Eight hours?

2.2

A. Correct. If you're using an asbestos product, and there's dust generated in the air, it's not all going to stay up there for eight hours. It won't happen.

What will happen is, is that over time it will start to dissipate because its fibers are running into the walls and into the ceiling. You have a tumbling effect, when these fibers are released and hit each other.

So it really depends on concentration, how much is there and how much is measurable.

We have done a study where we have measured, I think 90 to 120 minutes after the activity happened, and we're still seeing 10 percent of the fibers present in the air.

So they do stay suspended for a long period of time. That's in our studies.

MR. HARRIS: Excuse me, Your Honor.

Mr. -- or Dr. Longo is starting to give opinions now, and I don't want to interrupt Mr. Frost's exam. We have filed a Daubert motion challenging Dr. Longo's qualifications and reliability of his opinions. We just ask that the court reserve ruling on his qualifications to testify to the matters that he's going to testify about today, until the court has, at the end of the trial, or the court has an opportunity to consider our Daubert motion.

THE COURT: All right. We'll hear his testimony and deal with any of that other stuff later.

MR. FROST: Okay. And Your Honor, I guess I'll go ahead and offer Dr. Longo at this point, since there's been an objection, that Dr. Longo, at this point, be -- is tendered as an expert in material science, electron microscopy and industrial hygiene as it relates to asbestos.

MR. HARRIS: Your Honor, we have made our objection. We just ask the court reserve ruling on the objection until the court has an opportunity to hear Dr. Longo's testimony and consider our *Daubert* challenge.

THE COURT: We'll go ahead and hear his testimony. He can testify as an expert, and we'll -- as I said, we'll deal with the challenges later.

MR. FROST: Thank you, Your Honor.

- Q. And Dr. Longo, just so I do all the legal stuff, do you agree to keep all of your opinions today within a reasonable degree of scientific probability?
- A. Yes, sir.

Q. Now we were talking about asbestos and how long it can stay up in the air. Is this concept of re-entrainment and the fact that it's not just the folks working with the products, but it's people who clean it up later, and also for people potentially take it home on clothing. Is that something new in the literature, is that something Dr. Longo came up with?

1 A. No, sir.

- Q. How long have those concepts been known about asbestos?
  - A. I mean, some of the earlier studies where they're measuring exposure to workers in shipyards back in the '30s. The take-home exposure started to be published in the '60s.

So the measurement of asbestos and understanding about concentrations have been around for quite some time.

- Q. Now Dr. Longo, we were talking a little bit about protocols. Have you also worked with the ASTM and what is the ASTM?
- A. That's the American Society for Testing Materials. They develop protocols and standards in all types of testing. Everything from concrete, how hard the concrete has to be, or what the strength -- compression strength of it is an ASTM standard. To things like how many times a hinge on a door should open and close before it fails is an ASTM standard.

The area of -- the testing of gaskets, looking at is an -- there's an ASTM standard for that. For testing the gasket in its ability to -- on -- after it's been stressed and heated, there's an ASTM standard for that.

But the area I worked in was indoor air quality for ASTM, their committee. Which was developing standards for the measurement of asbestos.

And specifically I worked on the -- I was the lead author on the ASTM method for analyzing dust samples, using

transmission electron microscopy. I worked on it for five years. And when it finally passed -- and you have to understand there's over 30,000 members of ASTM. Any member can put a negative vote in and stop the method in its tracks, so you have to get the consensus of all these scientists, and that took a while.

But in 1996 -- 1995, I believe it was, the method finally passed the final committees and became a standard.

- Q. And the standard, did you receive any awards for working with the ASTM in coming up with this new standard?
- A. In 1996 I received the ASTM Scientist Appreciation Award for doing that work.
- Q. Now you've talked a few times about different microscopes and different techniques. Could you briefly tell us what types of microscopes does your facility have when we're dealing with issues of asbestos?
- A. Well, since you have that picture, we'll start with that one. That's our scanning electron microscope. It's an environmental scanning electron microscope. We also have transmission electron microscopes, there's one. We also have an array of optical microscopes. These optical microscopes include stereo microscopes for low power observation of samples 40/100 times.

We have phase contrast optical microscopes for counting asbestos -- counting fibers and using the NIOSH 7400 protocol.

We have polarized light microscopes for analyzing asbestos bulk samples. For asbestos content using the -- again, EPA method.

We have regular everyday microscopes that are typically used for looking at -- and polarized -- looking at fungus, mold spores for counting. So we have all the various types.

- Q. Does your laboratory have all of the different types of microscopes that any of the current or former asbestos standards would require when you're looking at air monitoring data?
- A. Yes.

2.2

- Q. Now we'll talk a little bit more about that in detail a little bit later. But you talked about some of the research you've done. What is a work-practice simulation?
- A. That's a study where -- as we use it, where a type of work practice that a worker would use when involved with either the application or removal of an asbestos-containing product.

A work-practice simulation is done under very controlled conditions. And it's under a -- and it's done in such a way that we are studying the procedures itself, as well as how the material behaves. What happens? Is it not releasing the asbestos fibers? Is it a small amount, or very significant amount? So we've done this on many products.

Q. Was that one of the things that was published in that

peer-review study, a work-practice simulation?

A. Yes.

- Q. Now before we get into the nuts and bolts of that, what are background levels of exposure to asbestos?
  - A. It's the concept of, if you do not have a source of asbestos. Meaning, if I'm not disturbing asbestos products in this courtroom, but I want to know what the background samples are when no asbestos products are being disturbed or no asbestos products being present. An air sample is taken to see what the "background levels" are.

So that if we want to know what's in the every day environment that is not associated with a source, you take an air sample and analyze it and you can make that determination.

- Q. And why is it important to -- if you're going to do air sampling and look at data to determine whether there is asbestos being released, say you're an individual at Bremerton Naval Shipyard and you're about to test whether gasket fabrication or doing other types of gasket work is increasing the level of asbestos in the air, why is it important to do those initial sampling?
- A. Well, today we always do that. Back in the '70s and early '80s you didn't see background samples taken as much, because they were typically looking at a particular type of activity.

So it's always good to have background samples, but it's Laura Andersen, RMR 704-350-7493

- 1 not uncommon for these historical analysis like Bremerton,
- 2 Dow, Shell and others, not to have the background samples. So
- 3 I don't look at that as a criticism.
- 4 | Q. Now, has their been publications -- I have the cutout
- 5 | from Dr. Roggli's book. Have you done work with Dr. Roggli in
- 6 the past?
- 7 **|** A. I have.
- 8 Q. And even though you guys don't agree on everything, I
- 9 think Dr. Roggli has published Dr. Nicholson's work in his
- 10 book that deals with this air quality, of whether background
- 11 | levels of asbestos throughout the United States. Have you
- 12 reviewed that?
- 13 | A. I have.
- 14 Q. And what is Dr. Longo's number that you use when you're
- 15 looking at background levels of exposure to asbestos?
- 16  $\parallel$  A. The number I use is 0.0005. It's in line with "Air in
- 17 U.S. School Rooms Without Asbestos". So I try to pick a
- 18 number that is not the lowest, not the highest of these
- 19 different sets of air samples.
- 20 Q. And --
- 21  $\blacksquare$  A. Try to be conservative as what we use as background.
- 22 | Q. And so what -- who -- who set that particular level, or
- 23 who published that level that you rely upon?
- 24 A. Well, the "Air in U.S. Rooms Without Asbestos" was
- 25 published in this book. And I have to go back to the original

data where that -- we looked at that, but where that came from.

- Q. So if you and I talk about whether the exposures are above background, we're talking above that particular level?
- A. Yes, sir.

- Q. Okay. Now, we talked about work-practice simulations.

  Could you describe what a -- in general, what you're doing when you do that work-practice simulation, just the highlights. We'll show the chamber in a minute. But what are
- 9 highlights. We'll show the chamber in a minute. But what are 10 you doing?
  - A. What we're doing is using, again as we discussed, where we're using common tools that tradesmen would have used when they were either installing or removing an asbestos-containing product.

And these asbestos-containing -- these are typical tools and procedures that these individuals would have used. If you're dealing with asbestos-containing joint compounds, the tools are -- if it's a dry product that they're going to mix it either with a -- what they call a potato masher or stick or electric drill with a mixer on it, we replicate those same types of work practices where we use those tools. Every person who ever installed joint compound and started with a dry powder had to mix it. And they always use these different tools. Once the joint compound is on the wall and dries, these tradesmen would have to sand it. So we replicate that

sanding activity.

1

2

3

4

5

6

7

8

9

10

11

14

15

16

17

18

19

20

21

22

23

24

25

So we look at and studied what is the most common techniques for either the installation or removal of asbestos product, and use those work techniques to determine if there is any exposure or not from asbestos.

- And how do you obtain these products? Because we're talking about stuff that wasn't -- hasn't been manufactured in a while?
- Well, it's usually -- on the plaintiff's side it's a lot harder. We have to rely on all kinds of ways to get that. It's -- a lot of times on plaintiff's the -- their clients 12 would have saved these products over time. They put them in 13 their garage or they kept them.

If it is things like flanges, or valves, we've been able to get with individuals who have -- I call harvest -- has removed large numbers of flanges and valves and we're able to obtain, we made site visits to get valves from museum, warship, USS Lexington. People that purchased these materials on eBay. So it's almost like antique time. You have to go around and try to find it.

When we have worked for defendants, it's a lot easier when they want a product tested, they have those products. When we did work for Carborundum, their black magic grinding wheel, they provided one to us. When we worked for General Electric and did work-practice studies involving one of their

hair dryers, they provided to us.

When we work for defendants and they want the product tested, it makes it a lot easier if they have the products they made.

When you're working for plaintiffs, you have to search more.

- Q. Do you all videotape these demonstrations?
- A. These simulations, yes, sir.
  - Q. Now we're going to show one of those videos in a little bit. But what is the concept of Tyndall lighting?
- A. It's the use of high intensity lighting that at a certain angle the high intensity lighting will usually scatter off microscopic dust particles of all sorts. And that scattering allows the human eye to detect the scattering.

So it's a way to visualize the presence of microscopic dust that's normally invisible to the naked eye.

- Q. And could you give me an example when I might see that outside of these videotapes? When would I might see Tyndall lighting in my daily life?
- A. You'll probably never see it outside, because of the way the light is. In your daily life if you're sitting by a window and the light beam's coming in and the room's a little dark, it's typically easy to see the dust particles that will appear in the light beam from the sunlight, then disappear.
- 25 That's probably the most common way to see Tyndall lighting.

If you want to see a demonstration of light scattering because the sky is blue, because of the scattering of blue light off the air molecules. Or why when the sun changes direction, goes from blue to start more reddish and yellowish colors as the sun is setting, that's because the light is now scattering off particulates. Primarily air pollution that's causing that color shift.

- Q. What about say I'm working in my garage and I am sweeping up dust, and things like that. What am I seeing then?
- A. Well, if you see the dust you're sweeping it up, that -that states that you're seeing a very high concentration of
  the dust.

If microscopic particles are in a high enough concentration, you can visualize that there's something there. You can't see the individual particles.

If I take a handful of respirable asbestos fibers, and I throw it up into the air, you're going to see very dusty material. Over time that concentration dissipates and it will go from being able to see it, to not seeing it.

Another example is cigarette smoke. Cigarette smoke is very high density right at the cigarette of the person exhaling the smoke. Very quickly though, after that person exhales the smoke, it goes, you can't see it. But if you walk in where somebody has been smoking just a minute or two before, you can smell it. And you're smelling it because of

the microscopic particulates that are still present that you can't see.

So if you see dust, we know those concentrations have to be very high in order for the particulates to scatter enough light in your line of sight that you know that something's present. But you can't ever see individual particles.

- Q. Now we've been talking about some standards over the years, the ACGIH standard, Dreson (phonetic), and those types of standards. Is there any kind of conclusions you can draw, though, if an individual says, you know, I did this work practice and it involved a product that contained asbestos and I'm seeing dust. Is there anything we can say in regards to those type of standards?
- A. If you're seeing dust, and it's an asbestos-containing product, and it's not under where you have high intensity lighting or you have -- you're working in an area where the sunlight is coming in at a certain angle, what you can say is, that that concentration of dust, asbestos dust you're seeing without any aid of high intensity lighting, is higher than five million particles per cubic foot.

You have to have that concentration much higher in order for you to see it. At 5 million particles per cubic foot concentration of asbestos dust, is going to be completely invisible to the worker, in my opinion, without some aid of lighting that is different than the normal, say sunlight

- coming in on the factory floor would have.
- Q. Now how small are these asbestos particles we're talking about?
  - A. Asbestos particles are typically measured, not in millimeters or inches or feet. They're measured in micrometers. One micrometer is one-millionth of a meter.

So if you were to take a meter and slice it evenly one million times, each one of those slices would be a micrometer.

The human hair, the width of a human hair is 100 micrometers. The width of a chrysotile fiber is typically about .04 to .05 micrometers. So the width of an asbestos fiber is many thousandths of times less than the width of a human hair.

14 | O. Less than a human hair?

be in, like, a thimble?

- 15 A. Correct. The width of a typical chrysotile fiber, not
  16 the length, but just the width of it, is typically thousandths
  17 of times less than the width of a human hair.
  - Q. Let's say I had a thimble of chrysotile asbestos fibers.

    Can you approximate how many asbestos chrysotile fibers might
    - A. Well, if you take a gram of short chrysotile fibers -- or excuse me, one microgram. One microgram would have somewhere in the neighborhood of 200 million. So one-millionth of a gram would have approximately 200 million fibers of chrysotile. A thimble full, half a gram maybe, quarter of a

1 gram.

So you're looking at billions, if not trillions of chrysotile fibers in a thimble full -- in a thimble full.

- Q. Now this Tyndall lighting that we were discussing, is this something that Dr. Longo came up with?
- A. No. It would be called different than Sir John Tyndall. Sir John Tyndall was a British physicist who developed this concept in approximately 1860. He was a British physicist. And the ability of microscopic particles to scatter light is -- that he developed, essentially is the basis of all the laser light scattering and measurement techniques for airborne

It's not something that I developed. I used a technique that other people have used.

particles that are used today.

- Q. And I have a slide up there. It's got Sir John Tyndall which we talked about. Says Tyndall lighting discussed in numerous textbooks. Where has Tyndall lighting been discussed in the literature?
- A. Textbooks typically, college chemistry textbooks because it's one of the techniques they talk about visualizing microscopic particles of all different sorts of liquid.

It has been published both in my paper, as well as in 1970 in another scientific journal. Many manufacturers of asbestos products have cited the use of Tyndall lighting, including Johns-Manville, Union Carbide.

It is a protocol that is published by the Health and
Safety Executive, which is in England called there, it is the
Dust Lamp, methods for the determination of hazardous
substances. That's all predicated on the use of high
intensity lighting.

The Environmental Protection Agency, in one part of their protocol uses Tyndall lighting to be able to visualize the re-entrainment of particles involved in some of the issues of vermiculite in homes.

So it's not an area that I came up with. It's an area that has been used by others.

- Q. And besides being used in basic science books and being cited by industry, cited by EPA, has Tyndall lighting been generally accepted in the scientific community as a concept?
- 15 A. Yes.

- Q. Now you talked about the EPA. That particular protocol, did you all, in doing your studies, have you followed some of the EPA's protocol?
  - A. Yes, sir. We -- we referenced the EPA protocol in our studies, because it primarily uses -- EPA talks about the use of a high-powered narrow beam spotlight, Tyndall lighting, in part of their protocol. So we reference that in some of our studies.
  - Q. Now, I also think that EPA protocol, if I remember right, talks about a particle counter; is that correct?

A. Correct. The entire protocol uses both high intensity lighting to Tyndall lighting. And then it uses a particle counter to take real-time particle measurements, and put those particle measurements on the video via computer.

We didn't use that part of the protocol, because we weren't interested in total particles, we're primarily interested in fibers. So we used another technique to measure the concentration of fibers in the study, not just overall particles.

- Q. And when -- we're going to look at the video, we're going to see when it's normal lighting versus Tyndall lighting. Is what we're seeing with the Tyndall lighting, is that all asbestos?
- A. No, of course not.

- Q. Can you explain what we're going to see here in a little bit?
  - A. You're going to see dust generated from work activity involved in removing an asbestos-containing gasket off a flange. This will be both scraping and hand wire brushing, scraping and electric-powered grinding.

That gasket that's being removed off that flange, has an asbestos content, I think somewhere around 70, 75 percent. In which is consistent with what the manufacturers say they put in these compressed sheet gaskets.

So the concentration of asbestos by weight and the dust,

Laura Andersen, RMR 704-350-7493

I wouldn't -- I don't think there's any reason to believe that it would exceed what was actually in the product, you get a mixture of whatever the materials are in the product.

If you're using a product that has 10 percent asbestos in it, it's my opinion that the dust that's seen in the Tyndall lighting will be approximately 10 percent.

If you're pouring raw asbestos, then what you're seeing in the Tyndall lighting is all -- is 90, 99 percent asbestos and some other minerals that may be in there.

So I believe it's dependent on what's in the material. So if it's thermal insulation and it's 15 percent, then the amount of asbestos in that visible dust cloud under Tyndall lighting would be approximately 15 percent.

Since these materials are homogenous in makeup, they have the ingredients mixed throughout. So there's no reason to believe it would be different other than what's in the product themselves.

- Q. So that's why it's important to look at the products themselves and how much asbestos they contain?
- A. Yes.

Q. Now does work-practice simulations, we talked about securing the exemplars of asbestos products. You determine what the workplace activities are. How do you do that, and what did you do in regards to the Garlock study -- I'm sorry, the gasket studies. How did you do that?

1 A. Well, we interviewed both pipefitters and steamfitters.

2 Read many, many depositions of steamfitters and pipefitters.

3 They all talked about three primary tools that they used.

There was some -- these three tools were typically a stiff

5 putty knife, a hand wire brush and a grinder.

4

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

The grinders were typically side grinders, either electric or pneumatic or air-driven grinders. Every now and then somebody would use something a little different, sander, sometimes you'll see filing. But by and large, the majority of these individuals would use those three tools.

So our work-practice study was based on the use of those three tools for gasket removal; a stiff putty knife, a hand wire brush, and a grinder with a wire wheel -- with a wire wheel on it.

- Q. And when you have individuals conduct that same type of work that you've either interviewed people about or found in descriptions of workers over the years, what are you collecting and how are you going about that?
- A. I'm sorry. Could you repeat that?
- Q. After you sort of determine the work practices, what -- what are you doing in the chamber, how -- what's that process?
- 22 A. I'm sorry. I misunderstood. In the chamber we're using
- 23 those same work practices. On a flange, either off a pipe
- 24 | flange or a valve flange, we first try to scrape as much of
- 25 the material off as possible.

The residual gasket -- and these are gaskets that have now been in place for some years. We don't know how long they've been in place. But they have been in place, and we use these techniques.

If it's scraping and wire brushing, again, as much as possible is scraped off the flange. Then the residue that is left on the flange surface is wire brushed off until you get the material off. For grinding, same thing.

Q. And I have up there, perform the work activity. Then it says, collect air samples.

What techniques are you using to collect the air samples and let's just refer to the gasket studies?

A. The air samples were collected using the NIOSH 7400 method, and analyzed by phase contrast microscopy, either by our laboratory or an independent laboratory.

The transmission electron microscopy analysis have been both in the past indirect transmission electron microscopy analysis, as well as the NIOSH 7402 method.

And then we videotaped the entire work practice.

- Q. And so what you're doing is, you're using standard methods that have been established by NIOSH in determining how asbestos is counted in these tests?
- A. Yes, sir.

2.2

Q. Now I have exposure characterization laboratory ECL. We got a diagram of it in a minute. But maybe it's easier to

just use the diagram. What are we looking at here?

2 A. This is the diagram of the room we do the studies in.

The room is 20 feet long, 15 feet wide, and 8 feet tall. The room has two filtered air intake areas.

What you don't see here is off to the one area of this room is a decontamination area and a shower area for when you're leaving after working with these products.

In order to have -- make sure that the -- if anything is released, asbestos is released in the studies, we want to contain it in the room and contain it so that the only avenue or escape out of the room is through the filtration system. So it uses negative air technology.

So the air exchange meaning, we're pulling air out of that room at a rate of approximately 200 cubic feet per minute. So the air has to make up what's going into the room. So you always have air going into the room, and then exiting through the filtration system.

It produces a slight negative pressure, but there is ventilation always going through this room while we're doing these studies.

- Q. Now we have the slide before the ventilation rate. Is that what you were just talking about? How often is that happening, is that air circulating in the room?
- A. It's always happening. From the time the study is started, until the time the study is completed, that we have

that air ventilation rate.

So what that's saying is, every hour the air inside that room is exchanged approximately four and a half times. Which is dilution ventilation. There's always going to be residual air that didn't make it out. So it's known as dilution ventilation.

- Q. Do you go and test that area before any studies to find out if asbestos is in the air, since we heard asbestos is everywhere?
- A. Yes, sir. We routinely take air samples before we do the study to see what's present, so that we know if there is any release of asbestos, we can compare it to what was in that room before.
- Q. Now we talked a lot about gaskets. Have you actually looked at the Garlock gaskets that contained asbestos prior to them taking it out?
- 17 A. Yes.

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

- Q. And are you familiar with the asbestos content of Garlock asbestos sheet gaskets?
- 20 A. I am.
- Q. And what was generally the content of those particular materials?
- A. They're generally around 70 to 80 percent by weight of asbestos, either chrysotile or the specialty gaskets, crocidolite.

- Now we talked about asbestos and their size earlier. 1 O. 2 is asbestos used in products? 3 Typically they're used in products to give it strength. 4 People think about -- and because it's heat resistance and 5 gives it strength. For gaskets, it's twofold, for its heat resistance and to 6 7 provide additional strength to the gaskets. Think of a lot of these products that use asbestos like 8 9 concrete -- not that gaskets are like concrete. But concrete 10 is very good in compression strength but not very good in 11 tension. If you put steel bars in it, it increases the 12 strength of the concrete.
- 13 | O. Right.
  - A. If you use asbestos fibers, which are fibrous, it provides additional strength to a lot of products. Thermal insulation is a good example.

Fifteen percent asbestos in thermal insulation does not give it any additional insulating qualities, but it enables the material to stand up to the fact that you can handle it, and put it on, and doesn't break. It gives it strength.

A lot of these products the asbestos was used as a binder to give a strength to reduce cracking on drying. If it's joint compound, fireproofing, this was used so that you could spray the solid material through a hose.

Very few products, actually the asbestos was used to Laura Andersen, RMR 704-350-7493

25

14

15

16

17

18

19

20

21

22

23

24

protect against heat, safety apparel would be one of those.

- Q. Now when you talked about steel being put in asbestos to strengthen it, how strong are these asbestos fibers?
- A. Well, steel being put in the concrete to strengthen it.

The tensile strength from an asbestos fiber has been calculated to be somewhere in the order of 60- to 70,000 PSI.

- Q. How does that compare to, I don't know, steel?
- A. It's higher than steel for the same-sized fiber.
- Q. So for the exact same-sized fiber, asbestos is stronger than steel?
- A. Yes.

Q. Now we want to talk a little bit about some of the studies you've done and talk about gaskets in general.

How did MAS begin to start studying asbestos in gaskets and what were those early studies?

A. The very first study I believe happened about 1996, 1997. We were approached by plaintiff's attorney -- and I don't remember who now, it's been so long -- to look at the issue of exposure during the removal of asbestos-containing gaskets.

There wasn't much literature out then. But overall the concentrations being reported didn't seem to make a lot of sense to me, in that if you take a product that contains 70 to 80 percent asbestos, and you grind it to the point where it's producing dust, abrading it, that you shouldn't see, in some circumstances, much higher results.

But we really didn't know, so we did a basic study where
we took a gasket and adhered it to a metal sheet. We actually
used epoxy to hold it in place. This was a gasket that had
not been used in any piping environment or any valve
environment. It was essentially unused asbestos-containing
gasket.

Q. I think I heard somebody complain about those early studies that you somehow glued them to the flange. Is that that epoxy that we're talking about?

A. Well, it's clear we did glue them to the flange to hold them in place. Then to the surface of the gasket, not where it was glued, we ran a wire brush over it and we also ran electric drill with a wire brush over it to see if any fibers were released.

One of the arguments was that the asbestos fibers are encapsulated in the synthetic rubber, and no matter what you do, that encapsulation keeps those fibers from being airborne or released.

My thought was that if we take a brand new gasket, it hasn't been subjected to high temperature, elevated temperature in pressure, so it has not become friable and degraded. If you have a measurable release of any significance on a new gasket, then enhanced, that must suggest that gaskets that have been in place for a long period of time that have degraded, become more friable, they should also

release to elevated levels.

2.2

So we did a fiber release study. And that was back in '96/'97.

- Q. So the first studies what you were just doing was taking a new gasket, putting it on a flange, and trying to see whether it was really encapsulated or not?
- A. It was a fiber release. If it's encapsulated and the fibers do not release are somehow coated, you shouldn't see anything.

It's immaterial if it was epoxied to a steel grid or not. We never suggested or believed out in the field that they epoxied gaskets in place. They wouldn't do it. It was just to hold the gasket in place. It wasn't intended to replicate what happens in a steam line. It was a fiber release study.

- Q. And at that point later you had actual valves from steam lines. But at that point when you were doing those early studies, did you actually have any of those things to work with?
- A. No, not that first study.

The second study we received two flanges from a plaintiff's attorney in Hawaii.

Q. Now, before we get much further, I want to talk about asbestos fabrication. Have you done studies where it's asbestos fabrication? What is asbestos fabrication? What are those studies?

A. It's typically known as secondary use of asbestos -- of asbestos gaskets. Where the manufacturer of the asbestos-containing gasket material, such as Garlock or John Crane, they'll make sheets of asbestos-containing gaskets. These sheets are typically five by five, sold in a roll. Some larger, some smaller.

2.2

Then if they're not prefabricated, meaning the manufacturer or some other entity makes the shapes needed, they're fabricated at the job site. These are usually done by the machinists or pipefitters.

What we did is look at one of the techniques. A lot of machinists, pipefitters, steamfitters talk about is using a ball-peen hammer to tap out the gasket from a piece of this sheet gasket. So they're using a ball-peen hammer to cut out the bolt holes, to cut out the inside and outside, inside diameter, outside diameter. So they're essentially cutting out a gasket to fit in a flange.

- Q. So they would take a sheet like that, that Garlock -that big sheet. Then they would put it -- skip ahead just a
  little bit -- over the entire flange area, and then they would
  take a ball-peen hammer and size it to fit that?
- A. Correct. This would be a ring gasket. So may not use a ball-peen hammer for this. But for a full-faced flange where they have to deal with bolt holes, as well as the inside and outside diameter, a lot of times, machinists, pipefitters,

steamfitters, will talk about using this technique where they
lay it over the entire flange, then they use that flange as a
template to cut out using the ball-peen hammer.

- Q. Okay. So they would just take the whole sheet, and this is just an exemplar of a flange. But they would put it over a flange, and then they would take a ball-peen hammer and hammer around it to size it and cut it to put it in?
  - A. Correct. That would be a ring gasket. This is a raised-face flange. So they wouldn't do it with this type of flange. They would do it with a full-face flange, such as on a bonnet gasket, or a full-face pipe flange. So there's different types of flanges where this activity would have been done.
  - Q. Now, these studies you've actually done that using Garlock gaskets?
- A. Yes, sir. That was, I believe style 900. That was the first study we did where we -- where I did the work.

  Placed -- we had the sheet of gasket material, we cut out
  - square pieces, and then laid that piece over the flange and tapped out the excess material. And we did that for four gaskets.
  - Q. And we have up there -- we'll go through a number of these charts, but let's do this at the very beginning. We have a range and then we have an average, and that's fibers per cc. What's a fiber per cc?

1	A. It's the amount of fibers found in one cubic centimeter
2	of air. A cubic centimeter of air is approximately the size
3	of a sugar cube. So when we took the measurements while this
4	work activity was going on, we made measurements of the number
5	fibers that were generated during the activity. It's always
6	displayed as fibers per cubic centimeter or fibers per cc.
7	Q. So you've done that for Garlock. You've done that for
8	John Crane. What were the ranges and what were the averages
9	that you found using MAS found?
10	A. Well, when we did the Garlock gasket

A. Well, when we did the Garlock gasket -asbestos-containing gaskets, the range of air samples showed
levels of -- this was just fabrication, without any additional
work, such as filing, was 1.1 to 1.5 fibers per cc. The
average of that was 1.3 fiber per cc.

When we did the -- when we did the study -- the John Crane fabrication was the first study we did. The Garlock was the second.

The John Crane fabrication study showed a range of 1.2 to 1.8 fibers per cc. Had an average of 1.6 fibers per cc. So it was very close.

Again four gaskets. Even though it was different manufacturer, the product had the same amount of the asbestos, roughly, and it was the same type of binder.

So when all these variables were consistent, even though you're using a human to actually do the work, the results were

- 1 | very close.
- 2 | Q. Are you aware I've got MVA fabrication ranges. Is MVA
- 3 Dr. Millette's group?
- 4 | A. It is.
- 5 | Q. Did they do the same type of testing of these gaskets?
- 6 A. Yes, sir. They did the John Crane, they did the same
- 7 activity that we did. And their results were only slightly
- 8 | higher. But within the range of air. These results are all
- 9 very close. So essentially three different studies doing the
- 10 same types of activities, the results are all very close.
- 11 Q. And in fact I think we got the MVA John Crane fabrication
- 12 range they found was 2.2 to 2.3 fibers per cc. And the
- 13 average was 2.2 fibers per cc. Was that what they found?
- 14 A. Yes, 2.25.
- 15 Q. 2.25. I'm sorry. Those are a little higher than yours,
- 16 | but are they consistent?
- 17 A. They are in the same range that we found, same order of
- 18 magnitude. So for this type of work activity, these results
- 19 are very close. And it's close because we're doing -- we can
- 20 control the variables.
- 21  $\|Q\|$ . And other than Dr. Millette, we have a slide that was in
- 22 part of your report. Have there been people outside of
- 23 | litigation that have done this type of work?
- 24 A. Yes. Here's a -- different companies. The Bremerton
- 25 study, Dow, Union Carbide, Hobby One, Hobby Two, which was,

again, Navy studies, I believe. Then Hunter Sales Corporation

One and Two which we're looking at -- they were looking at
fabrication.

So these are fabrication-type techniques where the materials are disturbed pretty good. Not all fabrication studies have shown these results. If you have fabrication where you're just using a cutter, and it's by hand, and you're not really impounding the gaskets to any degree, the results are much lower.

So, but here's a range of industry results from different groups.

- Q. And Dr. Longo, I know you weren't here, but one of the things I've heard is somehow Dr. Longo's or MAS' studies are not reproducible in regard to these fabrication studies. Do you think that's an appropriate criticism?
- A. No. We did two different studies, two different gasket manufacturers, but using the same techniques.

In the fabrication study, the variables are the same. Meaning, we have the same-sized flange. We have the same thickness in type of gasket. We have the exact same work practice. Those results were very close to each other.

When you're taking gaskets, old gaskets -- when you're taking gaskets that have been in flanges for numbers of years, the variables increased dramatically, so it's two different things.

Now this encapsulation theory while we're talking about 1 Q. 2 fabrication. Have you looked at that encapsulation theory in 3 regards to Garlock gaskets? 4 Well, not only their gaskets, but many different 5 manufacturers of asbestos-containing compressed sheet gaskets. Yes, I have. 6 7 What can you tell us about those particular studies, Ο. 8 encapsulation? Well, encapsulation, and the theory is that because it's 9 Α. 10 a synthetic rubber or rubber matrix, that the rubber somehow 11 is coating all the asbestos fibers to a degree that they're encapsulated, so they're not going to be released. 12 And I agree with that theory if you're just holding the 13 14 gasket. 15 But once gaskets are starting to be abraded in some 16 method, new gaskets where they're using -- cutting them is 17 more aggressive than say somebody just using a hand cutter or 18 snips, or the removal of these gaskets where they're abrading 19 gaskets that have degraded over time under elevated pressure 20 and temperature, you don't see that. 21 If these fibers remained encapsulated with rubber, it 22 would really inhibit the ability to analyze the fibers by 23 phase contrast microscopy, or transmission electron

Laura Andersen, RMR 704-350-7493

The results showed that many -- most of the fibers being

microscopy. You wouldn't be able to see the fibers.

24

25

released are not even associated with matrix materials, only with maybe particles or pieces.

2.2

You can't -- in my opinion, you cannot take a product that contains 70 to 80 percent asbestos and completely encapsulate it with 20 to 30 percentage synthetic rubber. It's almost the other way around.

What you have is a mixture. It's a mixture that mixes a synthetic rubber that is cross-linked through the process with asbestos. It's no -- and the asbestos does not react with the rubber, the synthetic rubber is inert.

So once you start creating dust from either the fabrication process or you're creating abrading wire brushing, grinding, creating that dust, these asbestos fibers are released.

A lot of the asbestos fibers inside those gaskets are bundles. These bundles have hundreds if not thousands of individual fibers.

The synthetic rubber can never penetrate through these bundles. It's like cabling in a conductor where you have lots and lots of cables wrapped very tightly together. The asbestos bundles are the same sort of thing. So it can't penetrate. When it's being abraded, those bundles are being ripped open. So it's impossible to encapsulate all these fibers. We don't see that in our studies.

Q. Now, we brought a valve. Can you tell me what this is, I

- 1  $\parallel$  guess, if I can hold it up.
- 2 A. It's not a valve.
- 3 Q. You're right. What is it?
- 4 A. It's a flange. It's a flange off a steam liner.
- 5 Q. Is this one of the materials you tested in your studies?
- 6 A. Yes, sir.
- Q. Let me just pull back and got some better pictures. But when we're talking about this encapsulation, you were talking about the fact that -- whether rubber is able to encapsulate
- 10 asbestos fibers that are stronger than steel.
- You were talking about fiber bundles. Can you explain to us sort of what we're seeing here?
- 13 A. Well, this was an asbestos-containing compress sheet
- 14 gasket that was placed on a steam line flange. We don't know
- 15 how long. And the flange was cut out of the steam line -- a
- 16 number of these flanges were cut out of the steam line. And
- 17 then we ultimately were able to purchase them from an
- 18 | individual by the name of Dr. Gay who took them out of a
- 19 warehouse or paper plant in Oregon.
- 20 Q. Now these steam lines that you've used and purchased from
- 21 | Dr. Gay, are you aware of who originally these steam lines
- 22 were offered to?
- 23 A. Yes.
- 24 Q. Who was that?
- 25 A. Garlock.

Q. And when was that time period when these original steam lines you used in your testimony were offered to Garlock for their own use?

- A. As I recall from the affidavit, Dr. Gay removed -- or had these flanges and valves removed in approximately 1994. We received them in 1999. In that period after he removed them, he offered them to Garlock, and they stated they didn't want them.
- Q. Now, that was, I presume, I guess, between 1994 and 1999 during the timeframe when Mr. Boelter was starting to do his studies; is that correct?
- 12 A. '94 to '99, yes, that would be in that timeframe.
  - Q. Okay. And so when we're looking at this steam line, and we're looking at this material in the middle. Is that the gasketing material that we're looking at?
  - A. Yes. If you could slide it over, we have both sides of the flange. What we have here is the gasketing material on both sides of the flange. What happens when the flange was broken open, the gasketing, the compressed sheet gasket material adhered so tightly to the flange surfaces, that when we opened the flange, the gasket failed in the middle of the gasket. So the gasket tore in half. Because of the tendency of the propensity of these compressed synthetic rubber sheet gaskets to adhere to these types of flanges under elevated temperature and pressure. So we just opened it, the gasket

tears in half. Okay.

2

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

- Then we were talking about encapsulation. What are we 3 seeing here when looking at this material here? What's that white stuff?
  - Well, that white fibrous material is actually chrysotile asbestos that was put into this gasket during the manufacturing process.

What looks like fibers, is actually very large bundles of chrysotile asbestos. If you remember, you cannot visualize single -- a single chrysotile fiber because it's too small. Being able to see these large bundles, that bundle has to be made up of literally thousands of individual fibers. demonstrates also, because you can see the chrysotile bundles, is that shows how this gasket over time has degraded. So you don't have the intermixed with the polymer matrix. This is just the degradation process of the synthetic rubber that holds the gasket together.

- So when we're looking at this, and we're seeing all those white materials, that's the chrysotile asbestos in the gasket?
- 20 Yes, sir. Α.
- 21 Okay. Now we had some pictures of flanges. Is this the Ο. 22 same type of thing that we're talking about that we just 23 showed on the flange?
- 24 That's the exact same flange. Α.
- 25 Q. Okay.

- A. This is before we cut it to size so we could fit it into a display box to demonstrate how these gaskets adhere, these asbestos-containing compressed sheet gaskets, how they adhere under these kind of conditions you find in a steam liner.
  - Q. These additional pictures, these are just close-ups of that same type of gaskets showing the adherence?
  - A. Yes, sir.

5

6

7

- 8 | Q. And that whiteness again we're talking about chrysotile?
- 9 A. Chrysotile. This is a raised-face flange again. And what we call phonographic serrated edges.
- Q. Now, have you also looked at whether these asbestos gaskets ever contained anything other than chrysotile asbestos?
- 14 A. Yes, sir, we have.
- 15 Q. And what studies have done?
- A. Well, specifically on chrysotile-containing gaskets, we have looked at the ingredients of the material using some specialized testing to determine if there were trace levels of amphiboles present in the gaskets.
- Q. And I think the court's heard a lot about amphibole asbestos. But what were you really looking for or what did you find when you were looking?
- 23 A. We were -- it's well known that -- just give some 24 background.
- It's well known that chrysotile deposits in Canada,

  Laura Andersen, RMR 704-350-7493

because of the geologist talk about, it has a tendency to have tendencies to form amphibole or tremolite, actinolite, and even anthophyllite asbestos as a contaminate of these chrysotile deposits, typically found in the serpentine rock.

We wanted to be able to test and determine if the chrysotile products like gaskets, if we were to use a specialized testing protocol, would amphibole asbestos be present in tremolite or anthophyllite. So we tested a number of gaskets -- we tested a number of gaskets over the years to make that determination.

- Q. Now I have a slide up there that says asbestos fibers in 1 gram of gasket. How many asbestos fibers, say chrysotile fibers, would be contained within 1 gram of a gasket?
- A. One gram, it would be more than the 160 billion you have.

  A better number would be in the trillions for 1 gram of just chrysotile.
  - Q. So if we're dealing with just 1 gram of a gasket, it's not that 160 billion, it's really in the trillions of fibers?
  - A. Yes, sir. Based on the work by the Environmental Protection Agency looking at how many chrysotile fibers -- short chrysotile fibers in a microgram or gram of material.
  - Q. Now we -- you did an analysis of gaskets. Have you actually done Garlock gaskets that you looked at?
  - A. Yes, sir. These are different Garlock gaskets that we received over the years.

- Q. What did you find in regards to the Garlock gaskets when you looked at the chrysotile percentage and then whether amphibole was detected in those particular products?
  - A. For the asbestos-containing Garlock sheet gaskets, each of the samples we tested we found trace levels of amphibole asbestos using a specialized technique called the Addison Davies method.

For that last gasket where none were detected, that was one of Garlock's nonasbestos gaskets, one of their newer ones. Blue Guard was the name of the gasket. So we didn't expect to find -- we used it as a control.

- 12 | Q. Why is that important?
  - MR. HARRIS: Excuse me, just a second, Your Honor.

    I object. I think Dr. Longo corrected this in his deposition.

    He did not fine anthophyllite in the second gasket as

    mentioned there.
- MR. FROST: We're going to talk about that in just a minute, Your Honor.
- 19 THE COURT: Okay.
- 20 BY MR. FROST:

4

5

6

7

8

9

10

11

13

14

15

16

- Q. And Dr. Longo, what I've done is reproduce one of the tables from your study, correct?
- 23 A. Correct.
- Q. And we were talking about the last sample, the asbestos-free. Why is it important to have a control like

that when you're doing these type of studies?

A. Well, it's always interesting to us to have something
that you wouldn't expect -- we didn't really have any idea of
what we would find in the chrysotile gaskets. But because
there was no chrysotile in the Garlock Blue Guard gasket, and
if our theory is correct that the source of the tremolite -source of the amphibole is from the chrysotile, then we
shouldn't detect any in that particular gasket. So we ran a

Q. Why is it important to do controls and blanks and things like that?

control. Plus we also run blank samples along with --

- A. Just to make sure we're not introducing some confounding factor into the analysis. And we're looking at trace levels here, so we want to be careful that we're not causing something else to be in that.
- Q. Now this Addison Davies method, is that something that's been published in the literature?
- A. It was published in 1990. And it's based partly on the work that was done by others in the late '80s, dealing specifically with this issue of trying to determine if chrysotile has trace amounts of amphibole in it.

Under normal analysis that we all routinely use, you'll very rarely ever see any tremolite, actinolite, anthophyllite, what have you, because of the concentrations it's at. What the Addison Davies method does, is that it removes all the

chrysotile. Think of it as looking for some needles in a hay stack. If you remove the hay stack which is all the chrysotile, it allows you to take a look at and see -- so it increases your ability to detect trace levels. That's what the Addison Davies method was about.

- Q. And is that a method that people like yourself use in the scientific community to try to figure out these questions of whether amphiboles are present?
- 9 A. Yes.

- Q. Now, Mr. Harris was asking about the anthophyllite in that second sample. Can you explain what we're looking at there?
  - A. Well, in the second sample we reported both tremolite and anthophyllite. There is actually an original report there was one anthophyllite fiber. We went back and did a more thorough analysis of it, and came up with the amphibole percent.

In the deposition we looked at the original data, and the one anthophyllite fiber out of the many amphibole fibers that were found, was not present in that particular sample. So that was an error of putting that on there. The supporting data did not have anthophyllite. That does not change the amphibole percentage. But anthophyllite -- that one anthophyllite fiber should not have been put on that chart.

Q. So within your original report there was a chart, is

Laura Andersen, RMR 704-350-7493

basically this same chart. And what happened was when you

- 1 went to underlying data that sustains the chart,
- 2 anthophyllite's not there but tremolite is?
- 3 A. Correct.
- 4 Q. Okay. Now Dr. Longo, how many reports do you think
- 5 you've done over the years?
- 6 A. Thousands.
- 7 Q. Does anything in that taking anthophyllite out, does that
- 8 change in any way that tremolite contamination or amphibole
- 9 being present in that sample?
- 10 A. No. Not at all. Amphibole percent is 0.016. It's not
- 11 | based on that anthophyllite fiber. It was based on the full
- 12 Addison Davies quantification analysis. Anthophyllite is one
- 13 of the amphiboles that can be found in chrysotile deposits.
- 14 But it does not change the overall results of that amphiboles
- 15 were detected in that Garlock gasket at all.
- 16 Q. In fact, Dr. Longo, if I look through all your reports
- 17 | and look at all the data you collected, can I find typos and
- 18 some other mistakes?
- 19 A. Yes, sir, you can.
- 20 Q. Does that mean that your studies are inconsistent or out
- 21 | of touch with what other people have done on these types of
- 22 | issues?
- 23 A. No, not at all. It doesn't affect the data whatsoever.
- 24 | Q. Have you ever done a perfect study?
- 25 A. Not yet.

- Q. Now, we were talking originally about asbestos fibers in one gram of a gasket. When we talk about these levels of amphiboles being present, is there any way for us to determine how much tremolite might be in a gram of gasket?
  - A. You can back-calculate using some assumptions from those concentrations. It obviously would be much less. Typically, if you back-calculate the concentration of the amphiboles in gasket materials typically runs between 100 and 150 million per gram.
  - Q. Now Dr. Longo, when you did these studies, you prepared a videotape that looked at what you were doing, correct?
- 12 A. Correct.

5

6

7

8

9

10

11

24

- Q. And we brought an edited version of that videotape to show the court. There is a video where it went through every second from the time you walk in the chamber until the time you walk out. And then there are versions where we've cut it down so that it's not hours and hours of tape, correct?
- 18 A. Correct. The video -- the study we're going to look at 19 is gasket four.
- 20 Q. Okay.
- A. There was hundreds -- there was -- I can't remember
  exactly how many minutes, but it was over 100 to maybe 200
  minutes of videotape. But that wouldn't be it.
  - Q. Let's go ahead and show the --

25 THE COURT: Why don't we take a break before we get

Laura Andersen, RMR 704-350-7493

1490 into the videos. 1 2 MR. FROST: Yes, Your Honor. 3 THE COURT: It's been a while. 4 Let's take a break until 25 after. 5 (A brief recess was taken in the proceedings at 11:13 a.m.) 6 7 (Court reconvened at 11:25 a.m.) Dr. Longo, I don't know what's happened, but during the 8 break somehow we got these red arrows on everything. So the 10 red arrows, that isn't something that when we watch the 11 videotape that you guys added or anything, right? It looks 12 like it's on my PowerPoint and everything? 13 It's gone now. Α. 14 Hey, it's gone. Perfect. Ο. 15 I can just tell you that Cameron my technical guy was just -- he had a sigh of relief at this point. He's recycling 16 17 the computer, but let's talk about a couple things so we don't 18 waste any time. 19 You've done, and we're actually going to view the study. 20 You've done a number of different studies and they're known by 21

the number of the study or the name of the product, correct?

Α. Correct.

2.2

23

24

25

And we have up there gasket study three, four, five, and the Crane Co. studies.

Generally, what have -- these work practices that we're Laura Andersen, RMR 704-350-7493

- about to see, is this the same type of thing you've done in all these studies?
  - A. Yes. Not only for gaskets, but we probably have done at least 100 to 150 different studies on different products.
  - Q. Okay. Let's go to the video now -- hold on for just a second.

MR. FROST: Your Honor, there are a few things that Dr. Longo is going to have to show during the videotape. Is it okay if he comes down --

THE COURT: Sure.

THE WITNESS: Thank you, Your Honor.

MR. FROST: Make sure you face towards the court reporter. But if you can come down in an area where you can demonstrate what we're looking at.

- Q. Okay. What are we looking at here, Dr. Longo?
- A. We're looking at inside the ECL, and we have a work table in the middle. This is one of the flanges that we received from Dr. Gay where he had individuals cut the flange out of the steam system.

Here are the high intensity lighting that produces the Tyndall effect. So these are 750 to 1,000 watt bulbs that are turned on periodically to take a look at what's in the air during the activity. So here's the tools. And it's just about ready to start.

Q. Okay. Cameron, go ahead and start.

(Video playing.)

2.2

THE WITNESS: This is what the air inside -- can we freeze it for one minute? Just back it up a little bit.

The Tyndall lighting is on. We're looking at what's visible in the air before we get started. You can see -- typically we see a few particulates, but it's nothing of any significance, before we get started.

Here the pipefitter is removing the bolts off the flange. This is -- the person doing this work activity was a retired pipefitter with over 30 years' experience. He also worked -- was a Navy boiler tender in the '60s. He was the one who did this particular work.

- Q. Now so you used -- this isn't Bill Longo doing this work. This is a career pipefitter who's done this work in the field?
- A. Yes, sir. This is study four. In studies, one, two and three I did the work. I'm not a pipefitter. Not a steamfitter. Never worked in the field removing gaskets or installing gaskets.

But for studies four, five and the Crane Co. study, we have this individual who had been doing this his whole career and is now retired.

- Q. So the work practice that he's showing right now using the putty knife and the flanges, that's what the pipefitter, the man who did it for his whole life is doing, correct?
- A. That's correct. The only instructions we gave

Mr. Holcomb was please remove the gaskets as you removed them in the field. We didn't give him any instructions on how he should do it, other than saying scrape these -- scrapers and wire brushes on these flanges.

Q. Go on.

A. Here's under the Tyndall lighting from just the scraping activity. Now you can see this dust concentration in this area. And that's -- and not in this area. That's because the light beam is culminated to, so it's got a low divergence. It's one of the things you have to understand is that this would be here too if we had light going through there. Again, he's scraping, he's using the putty knife to try to get off as much as he can off the flange before they -- as he said -- the activity was to remove as much as possible.

Again, using a hammer on the putty knife, that was his technique, not mine. But it seems to be a common technique that you see people use over and over and over.

Here's without the Tyndall lighting. This is what a worker would see. He would tell you that this is not a dusty operation. You can see a little bit of dust without Tyndall lighting here from the wire brushing. But then you can see what happens when you wire brush.

Now again as we talked earlier, this is not all asbestos. This is a mixture of composite, in my opinion, of the gasket. So the gaskets have 75 to 80 percent asbestos, I believe, and

that's -- would be the concentration by weight in air.

Here's without Tyndall lighting. Again, it answers some of the questions we had early on, why didn't people ask for masks. When they said it wasn't dusty, was it in fact really dusty and they couldn't see it. So it was a very valuable tool for us to try to understand these exposures.

Here's a gasket in a flange that's been opened. Here he's trying -- he's getting under the flange. This is a ring gasket flange which is in this particular case. And I think that might have been the nonasbestos gasket. But it still left a residue that he's scraping. So they always try to lift it off if they can. Again, he's wire brushing.

- Q. So the amount of force he's using, this is what pipefitter's doing, not what Bill Longo told him to do?
- A. No. I was -- here he's cutting the edges off so he can -- and these gaskets would lift off. A lot of these were serrated edges -- I mean serrated finishes.

And again, I think in this particular study we did four or five hand wire brushing. That's probably good enough. We can move on to save time.

21 | Q. Okay.

- 22 A. Go to the next part.
- 23 Q. Can you move forward to the --
- A. There's a lead in. This is probably the last flange we did.

Again, lifting off the gasket. Again, you can see how tightly adhered it is. These flange surfaces have phonographic serrated edges, which are essentially about tenth to a half millimeter. You can't get the gasket out of those edges, because the gasket seats and flows into it under high -- under elevated pressure and temperature. It's just --it's not possible to just lift it off and scrape it all off with a putty knife. 

- Q. Now one of the criticisms I heard was something about the fact that these serrated edges that somehow doing this type of work that the pipefitter is doing that would somehow damage these valves. Is that something you found?
- A. Again, we didn't see that damage. This is -- this again is a pipefitter doing this work. This is the same type of tools that pipefitters and steamfitters have testified years and years, read hundreds of these depositions. It's the same tools. I don't see the damage that's been reported that might happen. Again, they stick so hard these particular set of materials, the gaskets rip in half.
- Q. When we see that fibrous material, what are we looking at there?
- A. Those are very large chrysotile bundles.

Q. Now there's been some criticism, Dr. Longo, that during some of these tests, maybe some of the pumps may have flickered. Are you aware of any pumps failing during this

particular test?

A. In this particular test, no. We've had pumps fail or the filter is damaged, we don't report the results. Now it's not uncommon for these helium pumps to flicker red if the tubing gets bent a little bit from the movement. Flickering red is not the pump that has failed. If it continues to do that flicker it will go red and fail.

- Q. Now we have the wire brushing.
- A. Here again the gasket is being lifted off. He's lifting off as much as he can. He's scraping off as much as he can off the flange face. They have to do this before they put a grinder to the flange face. If you don't scrape off all the big pieces, when you put the grinder to the surface, the pieces will fly out. So you always scrape the surface to get everything off you can.

Now here's a grinder. More energy input. So the grinder is going to cause dustier levels. The grinding activity typically produces higher results than the hand wire brushing activity.

- Q. Is that a surprise?
- A. No, it's not a surprise. Once -- it's like sanding wood. But again there's all -- there's different factors that affect the concentrations. It's not just the fact that you're using a grinder versus a wire brush. The primary factor is how much of the gasket residue is left on the flange. That changes

I think if

- each and every time. You can have a little bit of gasket 2 stuck on a flange and use a grinder and the results are lower, 3 than if you have a lot stuck on the flange and you're using a 4 wire brush for extended period of time.
  - Now we talked about -- there was some question about whether one of the pumps had failed and whether it flickered or not. Is there anything from your report that you've seen where any of those pumps failed during this particular test?
  - there's a pump in question, there was actually results, and in each set of data, each individual has two pumps. So if one
- 12 pump fails, then the results of that one pump should be
- 13 completely different, way different than the other results.

Not in this particular test that I recall.

- 14 So again it's not unusual to see them flicker from time to It's when it goes red that they shut off. 15
- Now there also was a discussion about the fact that you 16 17 guys used a wire brush that had a guard on it. Have you seen
- that? 19 Α. Yes.

5

6

7

8

9

10

11

18

25

- 20 Q. Okay.
- 21 Electric wire brush. Α.
- 2.2 Ο. Okay. Cameron pull up the video of the wire brush. 23 Now when you very first started the test, how was the 24 wire brush -- what type was it and what was installed on it?
  - It was a steel wire brush that was installed on a

- grinder. And the grinder had a shield on it around the wire brush, and became very apparent that the shield was interfering with the movement of the wire brush.
  - Q. And Dr. Longo, we pulled a section of the videotape where it's the grinder not even touching the flange, and what do we see?
  - A. Well, you can see sparks coming from the grinder itself.

    If you look at the grinding of the flange, it looks like the flange itself is sparking.
  - Q. Go back again, Cameron. I'm not sure.

A. Which happens sometimes with the wire brush when they hit the bare metal. But what's really happening is that, as you see right there, is the wire brush is hitting the inside steel, and eventually that caused the grinder to burn down.

The grinders used after this, the shield was taken off.

- Q. Okay. So in the first one when the grinder blew up, which was one of the other criticisms I heard, it was using that shield and problem was is the shield was creating a problem with the wire brush to begin with, without being on the flange.
- A. Correct. Because the wire brush expends out because the flexible nature of it. The burnout of the actual grinder was not due to the pressure on the flange at all, it was due to the fact that it was being interfered with the guard.

So it was not because it was being pressed down as far as

- it can on the flange. You can see the sparks were from the actual guard. That never happened again after we removed the guard.
  - Q. Okay. And again, who's doing that work practice?
  - A. Again, this is Dean Holcomb doing this work.
- 6 Q. The pipefitter?
  - A. Yes.

4

5

7

14

15

16

17

18

19

20

21

22

23

24

25

- Q. I think you can resume your seat. Switch over. Okay.
  So we've looked at the videotape and that was for gasket
  four, correct?
- 11 A. Yes, sir.
- Q. And we have a chart up there that has the different ranges and average of the different studies.

Can you tell us what's the significance of sort of where we are in those ranges and how it applies to the studies that you've done over the past?

A. These are the four grinding studies. Study three was an electric drill that was a Skil .3 horsepower electric drill, had an RPM of 1,350 I believe.

Studies 4 and 5 and Crane Co. grinder were an angle arm grinder, RPM in the 10 to 11,000 range, much higher RPM. I think what is interesting here, is the lower RPM electric drill, 15 to 31 fibers per cc, are consistent with the other flange gasket studies, even though we were using a very high-powered -- much more higher RPM grinder. So it didn't

seem to be that the effect of the RPM was what was influencing the results, other than it was a higher -- let me back up.

Since the electric drill is at 1,350 RPM, the grinders used in 4, 5, and Crane Co. were approximately 11,000 RPM. We don't see a significant difference between using electric drill at 1,350. We have some of the upper ranges are very close to the others. The average is higher than gasket four, but lower than gasket five and Crane Co., but in that same range. Doesn't seem that the RPM of the grinder produces any additional bias or effect from the overall results.

- Q. And so what -- based on your studies when we're dealing with flange gasket removal using a power wire brush, what types of ranges and fibers per cc are we talking about have been found in your studies?
- A. The ranges we see here for power wire brushing for our studies. We've had a range from -- gasket four from four fibers per cc, to the grinder study on five, the 36.8 fibers per cc, which was higher than the rest of the studies, and is an unusual result for that, for that grinder study, because of the 36.8.
- Q. What explains that unusual result there?
  - A. Well, what, during the study, in gasket study five, the first four air samples were worn by Mr. Holcomb and Mr. Hatfield. They neglected to turn the pumps on during the first 10 or 15 minutes of the studies. When they went to

change out the air filters, they found that they hadn't turned the pumps on. They changed out the air filter. They turned them on and then took the -- during the rest period, and then went on to do the study. Those were the highest results. The highest results found was not during the actual work activity.

The area samples taken during the work activity were pretty much the same we've seen, but much lower than that.

We sent those air samples off to an independent laboratory. Those are the results that they found. We confirmed the results using the 7402 analysis. So that concentration is on those filters.

And I guess -- and it's the only -- out of all the sets of samples, it's the only ones we ever took during the rest period. So we can't say exactly why it's higher, other than the area -- the work area -- the actual during the work must have been much higher. But it's the reason we take air samples. We can't predict these results.

Asbestos is not a gas. Asbestos fibers, especially using tools, you can get different concentrations. And we haven't done enough rest period samples to try to understand what happened in this one particular set of samples.

So that grinder five for the four air samples out of the 70 to 80 air samples that were taken in that particular study, are somewhat different than the -- are different than the rest of the studies -- rest of the air samples taken.

- Q. So what happened was, is that the 36.8, prior to that sampling being done during the rest period when nothing's going on. There had been work activities being done, it's just those stopped, they figured out they hadn't changed the pumps. They start the pumps while they're resting, and those are those numbers from that --
- A. Correct.

- 8 Q. -- before the work practice?
- 9 A. I mean, the pumps weren't running, but they were grinding off a large gasket on a flange.
- Q. Okay. So it wasn't like they just walked in the room turned on everything and that was the number they got?
  - A. No. No. It was taken during the rest period. And out of the 500-some-odd air samples we've taken during all these difficult studies, I don't believe this is the only set taken during the rest period. We don't have enough data to understand why these particular numbers are what they are.
    - Q. How many total numbers of samples have you taken in these various gasket studies over the years?
    - A. Just in gasket studies alone, I think the number exceeds something in the area of 4- to 500 air samples. So it's somewhere in that area, quite a bit.
    - Q. And when we talk about those 4- to 500 air samples that you've taken, how many different data points are there that you've been able to look at based on those 4- to 500 samples?

Well, I went through and spent time looking at all the Α. data points for gasket studies two, three, four and five, not the Crane Co. And in looking at all the individual data points, looking at all the individual entries, all the recording for everything that was done, I came up with an estimate of a little bit over 50,000 individual data points from the charts, to the recordings, to the actual analysis, to the individual fiber analysis, everything. 

So if you were to put the Crane Co. study in, which is just about as large as all those studies, you know, it's going to be somewhere in the 70 to 100,000 individual data points.

- Q. And Dr. Longo, based on your studies, if an individual was doing the fabrication of asbestos-containing gaskets, doing the typical work practices back in the 1950s, '60s, '70s, during those timeframe using those typical work practices and things that you've studied, would those individuals be potentially exposed to asbestos in excess of that background level we talked about earlier?
- A. Yes, they would.

- Q. And when we talk about not using the power wire brushing, but taking the flange, opening it up, cleaning it with a putty knife, and then taking a wire brush by hand, would that have potential for individuals to be exposed to above background doing that work practice?
- A. Yes, sir. I don't remember if I saw the slide, but there

  Laura Andersen, RMR 704-350-7493

is -- was a slide on the concentrations of just scraping and wire brushing.

If you look at all our studies, the ranges of scraping and wire brushing on flange gaskets was approximately 0.4 fibers per cc for gaskets that just fell off pretty easily and only had a small amount of wire brushing that was required, to a very large flange that the gasket was adhered very tightly up to, I think it's 20 to 21 fibers per cc.

If you were to average all that out, the range of exposures for wire brushing on the order of about two to four fibers per cc. So much lower than the ranges you see for the power wire brushing.

- Q. And again, if we're doing -- if an individual was doing power wire brushing of an asbestos-containing gasket, would those individuals have potential to be exposed asbestos above that background level during that work practice?
- A. Yes, sir. Be my opinion that if you have to grind residue off a flange surface, asbestos-containing residue to any degree, you will be above background levels.
- 20 Q. What would that range be based on your studies?
  - A. On our studies we've seen the range where you -- of .3 to .4 up to 21 fibers per cc.

In fact, if a gasket just falls off, the range can be very low. It's all about how the gasket sticks, and how much of the material has to be removed, if any.

If a gasket comes out intact, and there's little to no residue on the flange, I wouldn't expect to see very significant results at all from the actual wire brushing or using a grinder to polish -- polish the flange surface.

studies show that.

Q. Now Dr. Longo, one of the things we've heard in this trial was somehow Dr. Longo's results have not been replicated. In fact I think someone said even you can't replicate these results. Is that a fair criticism?

A. No, that's not fair at all. The ranges of exposures for different types of activity, power wire brushing, is in the same averages that we're seeing. What I said in my report was, that I would expect if you're power wire brushing off material off a flange, that typically you would be exposed to

fibers greater than 10 fibers per cc. Every one of our

But you have so many variables on a flange. It's very hard to take a flange from the source, remove the gasket. And if the gasket adheres to the flange to any degree, you say, okay. I'm going to get these same studies over and over -- same results over and over again. It's impossible. The reason is, there's so many variables.

The size of the flange. Is this a 2-inch pipe or a 10-inch pipe. The size of that flange, is it a full-face flange where it covers the bolt holes or is it a ring flange -- excuse me, a full face gasket that covers the flange

where the entire inside of the flange has a gasket material on it, or is it a ring gasket that is on a raised flange. Is it a serrated or phonographic surface versus a flat surface. Is the gasket a 1/32nd of an inch, 1/16th of an inch, or 1/8th of an inch. How long has the gasket been in place? What temperature has it been under? These are all variables unknown.

The only way you can do something is to take in test procedure, take a flange, put a gasket in it, put it in a steam system, everything the same, same person doing the work, and your results would probably be almost on top of each other. But to say these results are not reproducible, I think is unfair.

What our results have shown is that repeatedly that we get these same magnitude of results, and it all depends on the gasket. I've always said this a lot of times. Not one study from any individual can replicate every condition ever experienced by a pipefitter, steamfitter, what have you, because of all these variables.

You're going to have in some cases where the gaskets just fall off. Those are -- exposures are going to be very low. In other cases you have gaskets that adhere like ours did in some of these where they split. Those exposures, depending on the tools, will be very significant. And you can have everything in between.

There's no one study that can say, this is what happens to everybody. This is -- some are going to be very low exposures. Some are going to be somewhat significant, and some will be very significant.

- Q. Now there was some discussion with Mr. Boelter, and that's a still from the video that we looked at, correct?
- A. Yes, sir.

1

2

3

4

5

6

7

13

2.2

23

24

25

- 8 | Q. Okay. That's using the Tyndall lighting?
- 9 A. Correct.
- Q. Now, there was some discussion with Mr. Boelter about the Cheng and McDermott study the one Chevron Corporation did and was published in the literature in 1991. You're aware of that
- 14 **∥** A. I am.

study, correct?

- Q. There's a table, I guess I should have blown it out better. But it has dry removal of gaskets and valve gaskets, and it has the samples and it has concentrations. Are you able to read that on the screen that you have?
- 19 A. I can.
- Q. Okay. How do those concentrations compare with the studies that you've done?
  - A. They're at the lower end of our work. We have studies of .3, .41, one to two, two fibers per cc on some of the gaskets that didn't adhere very tightly. So these results are -- let's see, two valve gaskets .1. Our results -- our

- lower end results are .3 to .4 on up. We don't have results 2 as low as .1 to .2.
- 3 Are they statistically -- I won't say statistically 4 significant. But is there any real huge significance here that these here are a little lower?
- They're all significantly above background. 6 7 all less than one fiber per cc. Because of the sampling and because of the size, it's not unusual even on the same person 8 to have air cassettes that are double from one side to the 9 10 other, depending on which side is facing the flange, et 11 cetera.
  - And is it uncommon for labs to do a test and do it in a certain way, then replicate the test again and come out with different numbers?
- 15 No, it's not uncommon at all.

5

12

13

14

18

19

20

21

22

23

24

25

- 16 Why does that happen when we're talking about asbestos 17 and this type of work?
  - Well, you got to remember, asbestos is not a gas and there's a human being doing the counting. So it's not unusual, that's why for round robins they give such a big spread for what's considered okay to pass. Nobody has ever had a round robin where all the labs come up with exact same number. There's always a whole range. Then they look at that range and they decide what is acceptable. That concentration from .1 to .3 for a round robin would have been acceptable for

- lacktriangle the same air samples.
- Q. So those would have been acceptable and within what you
- 3 would expect based on both work?
- 4 A. Correct. Say the sample that was sent around was
- 5 actually .3 or .2. If every lab in the country gave a result
- 6 that was between the .1 and the .3, the results would be so
- 7 | narrow that those all would have been accepted as passing the
- 8 round robin.
- 9 Q. Now you're aware Dr. Millette's also done some studies on
- 10 asbestos-containing gaskets?
- 11 A. Yes.
- 12 Q. This was published in the EIA technical journal in 1995.
- 13 That's something you're familiar with, correct?
- 14 A. I am.
- 15 Q. We talked with Mr. Boelter about this, but they actually
- 16 during that test, they used masks and respiratory protection,
- 17 correct?
- 18 A. Correct.
- 19 Q. When you did your test, did you use mask or respiratory
- 20 protection?
- 21 A. Yes, absolutely.
- 22 | Q. Why?
- 23 A. Well one, we don't know what the results are going to be.
- 24 So out of prudence, and unless you absolutely know the results
- 25 for those particular workers and that particular work site,

- you have to have a respirator. Number one, to me it's common sense. And number two, it's an OSHA requirement.
  - Q. And in fact, were there not some gaskets that were made out of crocidolite?
    - A. Yes, for specialty occasions, such as acids where normal chrysotile gaskets will not hold up.
  - Q. Are you aware that Garlock made some of those gaskets?
- 8 A. Yes, sir, I am aware of that.

- 9 Q. Now, Mr. Millette published also some of his studies and
  10 we're talking about power wire brushing, and we're talking
  11 about this issue of whether Dr. Longo was out of the norm.
- 12 These were his numbers. How do your numbers relate to those 13 for power wire brushings?
  - A. We've had sets of air samples done in that range for power wire brushing. Again, it just all depends on what the gasket is like that you're dealing with. So that's almost 6.8 fibers per cc in our gasket four study. We had a set of air samples four to seven fibers per cc.

For hand scraping and power wire brushing, they have 2.1. We have recent studies that show two, two and a half fibers per cc.

So it's not so much that we can't reproduce each other, the problem is what we're starting with is different from every lab that looks at the valves. You can't -- you're taking valves out of the system that over the years have had

different temperatures, different pressures. When was the last time the gasket was put in. You don't have any consistency on what we're getting to test. So you can look at trends.

Scraping and wire brushing, you're going to have lower levels typically than -- we found than power wire brushing or power grinding. And the results are in these ranges. These are some of the lower end results that we found, but they're in the ranges that we found.

- Q. And so when we're talking about whether your results could be replicated or other people have found those types of things, we didn't talk about the hand scraping and power wire brushing. They're different numbers for the different activities and that -- those are consistent with your numbers?

  A. Correct. Now scraping and power wire brushing shouldn't be that much different than just power wire brushing. But if you're dealing with a flange that the gasket would adhere to the flange after the bulk of the gasket been removed much less, you're going to have much less, even if you do that same technique over and over again.
- Q. Now I think there was some discussion with one of the earlier witnesses, I think it was Mr. Liukonen, about the TEM results. And I think he indicated that he didn't think the TEM results could be higher than the PCM results, is that true?

A. No, that's not true.

2.2

- Q. Can you explain that to us, why it's not?
- A. Well, the TEM analysis that Dr. Millette has done here, is a standard structures per cc analysis of asbestos fibers, the PCM is in fibers per cc.

The PCM, because it's an optical microscope at a magnification of 430 times, only can see the very biggest bundles of chrysotiles. So the fiber has to be longer than five micrometers in length, and wider than .2 to .25 micrometers in width.

No chrysotile fiber that has been mined out of the ground anywhere in the world, has widths of that size. So what you're looking at is bundles.

Now that size of bundle or fiber is a very small fraction compared to all the asbestos that's present. Asbestos fibers that are less than five micrometers would not be counted by PCM.

Single asbestos chrysotile fibers that are less than .2 micrometers wide, would not be counted by TEM.

So the TEM results where you're counting all the asbestos present is always going to be higher, typically. And the numbers floated around depends on the product, but it's usually anywhere from 10 to 20 to 30 times higher, in that range.

So it's not surprising at all that all the TEM results

Laura Andersen, RMR 704-350-7493

- are much higher than the PCM, because you're looking at all the asbestos fibers, not just the very biggest ones.
- Q. So the TEM method itself, even though it's doing
  structures per cc, the reason you're using that is that it's a
  more precise method and it's going to see more?
- A. Correct. It's looking -- I don't get in the argument
  what's important in health. But that's what's really in the
  air when you're doing TEM analysis. It's giving you a
  snapshot of all the size fibers.
- Q. I think that's what Mr. Millette wrote in his article.

  He talks about the TEM and the analysis of those sheet gaskets

  which he said were 80 percent; is that correct?
  - A. That's correct.

13

14

15

16

17

18

19

20

21

2.2

23

24

25

- Q. Now he also talked about this issue of friability, and says that "asbestos sheet gaskets, although not considered friable in original unused condition, can release asbestos fibers into the air during various operations when hand methods are used, and especially when power tools are involved. Clean-up following cutting of new gaskets and removal of after-service gaskets may be suspended as dust-containing asbestos into the air." That's that re-entrainment that we talked about, correct?
- A. Yes, sir.
- Q. That's if someone had done valve work and blew it out with air and someone swept it up afterwards, that type of

1 | thing?

A. Yes. He showed in his study the levels were -- what we found in a lot of our work, not just gaskets, thermal insulation studies, brake studies, that the clean-up typically can be as high as the actual exposure during the work.

So the finding of 5.5 fibers per cc, which is almost as -- higher than the hand scraping and power wire brushing, but lower than the power -- just power wire brushing, is consistent with all asbestos products across the board where the clean-up can be as high as the actual use of the product.

- Q. And I think that -- now -- and then this is your study. But then have there been other people who looked at the same types of things. We have the IHF study from 1978. Are you familiar with that?
- A. I am.
- Q. What's the significance of that type of study and who was it done for?
  - A. This was done for Garlock, and it's the removing a gasket from a flange, and the significance of it is it's 4.58 fibers per cc. They don't state that they were using hand wire brushing or grinding. But it does show very significant level of exposure, and is in the range of some of our -- both our -- almost the average of our hand wire brushing studies, and one of the lower-end samples for power grinding.
  - Q. Now, this study done by the Industrial Hygiene

- Foundation, it's in 1978 for Garlock, are you aware of that ever being published in the peer-reviewed literature?
- 3 A. No, sir. You typically don't see these types of studies
- 4 | in the peer-review literature. Every now and then like
- 5 Chevron allowed that to be published, but it's somewhat rare.
- 6 Q. So the study that was done for Garlock using Garlock
- 7 materials, is that consistent in the ranges that you and I
- 8 have been talking about?
- 9 A. Yes, sir.
- 10 Q. Now you're familiar with the Shell study from 2005?
- 11 A. I am.
- 12 | Q. And we're again talking about this issue of whether your
- 13 research is consistent with not only what's been
- 14 peer-reviewed, but what's going on in industry. What can we
- 15 learn from the Shell study?
- 16 A. The Shell study, it was a Durabla gasket. And they tried
- 17 | two techniques to remove the gasket -- asbestos-containing
- 18 gasket. One, they used a grinder, like an angle grinder, I
- 19 believe it was a grinder. And they recorded results 28.4
- 20 | fibers per cc, that was in the range of our grinding studies.
- 21 Then they tried something unique that I've not ever seen
- 22 before. They did the study again where they used an acetylene
- 23 | torch to burn the gasket off, to see if they could reduce
- 24 | fiber levels. It was the first time I've ever seen that
- 25 anywhere.

- Q. I think I misspoke. It says 2005, it's actually 1985,
- 2 correct?
- 3 A. Oh, I didn't even catch that. You are correct.
- 4 Q. It was a late night last night.
- 5 A. Sorry. I should have caught that.
- 6 Q. But that's from 1985, correct?
- 7 A. Yes, sir.
- Q. Now you were talking about the burning of the gasket that you've never seen before. Any significance to that when we're
- 10 | talking about potential exposures to asbestos?
- 11 A. Well, when they removed the gasket from a flange using
- 12 acetylene torch, they actually got much lower results, like
- 13 0.5 fibers per cc. So it showed that -- but I don't think
- 14 that was very practical in the industrial world or on a Navy
- 15 ship.
- Q. Now, are you aware of this Newport News study again in
- 17 | 1982?
- 18 A. Yes.
- 19 Q. And what's the significance of that particular study?
- 20 We're looking at the first portion where it says "removing
- 21 | asbestos gaskets from steam valves with power tools"?
- 22 A. What's significant here is that the study is interesting
- 23  $\parallel$  in that they opened the valves -- they opened the flanges,
- 24 then soaked them with rags with water for 24 hours. They did
- 25 | this in an enclosure, but they did it right in front of a

ventilation hood. They first did work, then they used a needle gun to get the bulk of the asbestos off the gaskets -- I mean off the flanges. Then they used a power grinder to remove the residue.

They had a peak exposure of 29 fibers per cc. Then they had two samples that were too overloaded to count. If you're looking at overloaded samples to count, at least I have always made the assumption, if you have a series of samples and two of them are overloaded, but you can still count the sample that has 29 fibers per cc on it, then the overloaded sample has to be at least that high or higher. It has to be. You can't have a lower air sample with the same product, the same material, the same tools, except you're using a needle gun, and be overloaded and be at lower concentrations.

- Q. I don't think we talked about what an overloaded sample is, what's that?
- A. Overloaded sample is it has too much fiber in particular to count. Think of it as a plate of spaghetti. If you got a bowl of spaghetti, it's impossible to tell you other than there's a lot to tell you how much strands are in there. If you spread that spaghetti out, or you reduce the amount of spaghetti you put in the bowl, than you can more likely count. So an overload is just too much material there to actually analyze.
- Q. Let's say I have an overloaded sample. Can I take that

  Laura Andersen, RMR 704-350-7493

- 1 overloaded sample and then try to do some statistical analysis
- 2 to it to try to figure out how much asbestos was really there?
- 3 A. No.
- $4 \parallel Q$ . Why not?
- 5 A. You can, but it's not allowed.
- 6 Q. It's not allowed?
- 7 A. No. If you have an overloaded sample and you're trying
- 8 to determine OSHA compliance, what OSHA tells you to do, you
- 9 got to do it again. And that's in a work study work place.
- 10 When you do these work practice studies, you're not dealing
- 11 | with OSHA compliance, at least we weren't because we're
- 12 wearing respirators. So we usually have a one-of-a-kind
- 13 | sample, we can't go back. So we try our best not to overload.
- 14 Q. Now again, what were the results of that Newport News
- 15 | study with that grinding?
- 16 A. Well the grinding showed levels of between 10 and 29
- 17  $\parallel$  fibers per cc, if that is the grinding part. The needle gun
- 18 part, I believe it was the one was overloaded, we have to look
- 19 at the individual air samples.
- 20 Q. And then there was some discussion about what actually
- 21 | happened before the needle grinding. Have you looked at what
- 22 was going on in the very beginning of this study?
- 23 A. Yes, sir. Talked with Mr. Harris about this in my
- 24 deposition. The -- if you go back and look at -- if you go to
- 25 the -- no, you can leave it there.

- We have a set of samples that -- oops -- you know what, did I do that? I touched the screen.
- 3 0. That's what it was?
- 4 A. I did do it.
- 5 Q. You're the culprit.
- 6 A. I'm so sorry.
- 7 Q. That's okay.
- 8 A. I didn't realize this was a touch screen.
- 9 Q. I think you're the first person to touch the screen 10 because we haven't seen that yet.
- 11 Okay. So you were --
- 12 A. If you look at -- if you can see it -- it's kind of hard
- 13 to see. All right. The lower right-hand corner goes through
- 14 and tells what happened at different times.
- 15 Q. You mean this area right here?
- 16 A. Right. So from seven to nine they set up and put on the
- 17 clothing and set up the study.
- 18 Q. Right. It says, set up of area and looks like donning of
- 19 PP --
- 20 A. I think that's personal protection clothing.
- 21 Q. -- clothing. Okay.
- 22 | A. From 9:40 to 10:00, and actually it was from 9:40 to
- 23 9:58. For 18 minutes they went into the area and began work.
- 24 There's no description of what beginning work means. Now the
- 25 I flanges were already opened. The flanges were in front of --

in front of the air hood. So either two things happened. Either the individual entered and for 18 minutes just stood there, or for 18 minutes they did work.

Now the common technique of removing gaskets is to start off with a putty knife and material to remove much of the bulk material as possible.

He went out -- out of the room from 10:00 to 10:30 and obtained a needle gun, and then went back in and entered and removed the gaskets.

So we have a reading there of 5.8 fibers per cc during that 18 minutes when he said he began work. We don't have a good description of what "began work" is. It doesn't seem sensible to me that the individual said where they began work just stood there for 18 minutes and did nothing. So -- but I don't have a good description of that.

But it would fit the criteria of what machinists and pipefitters do is, before you use a power tool on these gaskets, you have to remove all the -- much material as possible. Because the power grinder lifts the large pieces that can be removed, will actually fling that material on the grinder. At least that's what the pipefitters and steamfitters tell me.

- Q. So basically that 284, that's that time period at the very beginning --
- A. The 18 minutes.

2.2

- Q. The 18 minutes. That's the sampling that's done. We're not sure exactly what was going on. We know that opening up the flange and testing, that's what they got?
  - A. Well, they had already opened the flanges. The flanges, if you read the study, so he said they began work. What work did they do if the flange is already open? If it's sitting in front of the hood, you know, my thought is, is that what they're doing is doing the scraping portion of it.

Now, when we get to the power tools, we can see how that increases for the residue material. The needle gun looks like it was way too heavy, and then we have the additional samples that were done.

- Q. If that 5.8 is when they're doing scraping, is that consistent with the scraping type studies that you've done?
- A. Well, whenever we've done scraping by itself, we've never done scraping and removal by itself. There you have a large number of flanges they were working on here. But again, I don't have a great description of it. But I don't believe when they said they began work that they just did nothing and that was the background air sample concentrations.
- Q. Now, in addition, are you familiar with Dow Chemical doing a study of gaskets?
- A. Yes.

Q. And just briefly, how does that fit into this realm of your studies?

- 1 A. The grinding study was, they found levels of 18 fibers
- 2 per cc, which is in the range of what we found.
- 3 Q. Now Dr. Longo, you are familiar with other people who
- 4 have done similar types of studies in the past, like
- 5 Mr. Boelter and Mr. Mangold, correct?
- 6 A. Yes, sir.
- 7 | Q. Have you actually reviewed their videotapes in the
- 8 context of litigation involving Garlock in the past? Because
- 9 you have testified for a number of years, correct?
- 10 A. Yes, sir, I have.
- 11 Q. I have up on the screen, a split screen. Is this
- 12 something you've seen on the past?
- 13 A. Yes, sir, I have.
- 14 Q. On the right-hand side it says, MAS. On the left-hand
- 15 side, what is that?
- 16 A. That's Mr. Mangold during his gasket removal study. I'm
- 17  $\parallel$  the one who put this together so I'm familiar with it.
- 18 Q. Okay. So this particular video that we have is basically
- 19 a side-by-side of your study, and then Mr. Mangold's study,
- 20 | and then a little bit later Mr. Boelter's study, correct?
- 21 A. Correct. This is some of the work activity that
- 22 Mr. Mangold did when he was removing a gasket. And it was
- 23 | compared -- I wanted to compare it to our study. So initially
- 24 when we got our results, it was clear to us in the early years
- 25 that Mangold and Boelter hadn't published their work yet, but

- 1  $\parallel$  I was familiar with it, because I had seen the results. That
- 2 our results were 180 degrees different from theirs. Ours were
- 3 | much higher. I was trying to understand why. These
- 4 | videotapes helped understand why there could be such a
- 5 difference between their work and ours.
- 6 0. So if I show these to someone later in the trial, what's
- 7 going on on the right-hand side is your testing. What's going
- 8 on on the left-hand side is Mr. Mangold and Mr. Boelter's test
- 9 that you've seen?
- 10 A. Yes.
- 11 Q. Okay. Now I want to talk to you about another issue,
- 12 | just very briefly is -- there's been a lot of discussion about
- 13 what you do as being junk science and that there was a court
- 14 in Lamar County that excluded some of your testimony. Are you
- 15 | familiar with that?
- 16 A. Yes, sir. To be fair, excluded all my testimony.
- 17  $\parallel$  Q. And there's been some allegations that basically --
- 18 you -- they call it junk science, I guess. Have you heard
- 19 that in the past?
- 20 A. Yes. The judge actually in that order called it junk
- 21 science, so that's where they get that from.
- 22 Q. Now immediately after that order, have you been deposed
- 23 on your studies in the past?
- 24 A. Yes.
- 25 Q. Have you been deposed over many hours and many days over

- l | your gasket studies, things like that?
- 2 | A. I can't imagine how many hours I've been -- sat
- 3 | through -- I've been deposed on our gasket studies.
- 4 Q. And I know you and I have sat through a few of them. But
- 5 after the Lamar County Order, was there a Texas MDL concerning
- 6 asbestos organized?
- 7 A. Yes, there was.
- 8 Q. Has this issue of whether your studies are allowed in the
- 9 State of Texas been dealt with by the asbestos MDL judge?
- 10 A. Yes, sir. Judge Davidson, when he took over the MDL, he
- 11 was the gatekeeper for all the trials happening in Texas. As
- 12 you can imagine, the Lamar County Order came up immediately
- 13 with my studies.
- 14 Q. And subsequent to that, have you been allowed to testify
- 15 and use your studies in the State of Texas in the asbestos
- 16 MDL?
- 17 A. Yes. The MDL judge ruled that the defendants couldn't
- 18 use the Lamar County hearing decision in any case in Texas.
- 19 Q. Now, in fact, after that Lamar County Order, I want to
- 20 make sure I get the timing right. When was your study
- 21 | actually published in the peer-reviewed literature?
- 22 A. It was published in January of 2002.
- 23 | Q. After the Lamar County Order?
- 24 A. The Lamar County Order came out on July 5th,
- 25 approximately 4:00 p.m.

- Q. A day you remember well, I guess?
- 2 A. Yes, sir.

- Q. Now, what defendant was involved in that case and what law firm was involved in that hearing?
- A. The hearing was in RE. But the attorneys representing Garlock, Mr. Ray Harris was involved in that hearing.
- Q. And so the Lamar County part of that was Garlock's challenges to your gasket studies, and some of the same issues
  I'm sure we'll hear about this afternoon, were some of the same issues that were brought up in that study -- in those hearings, correct?
  - A. Yes, sir. They haven't changed much. And so the actual studies that we talked about, studies in the Lamar County hearing, studies two and three, two was hand wire brushing, MAS gasket studies three was hand wire brushing and electric wire brushing. Those exact same studies that, exact same data was published in one of the more prestige peer-review industrial hygiene journals. Took me a long time to try to figure out or reconcile why on the one hand judge clearly stated in a 12-page decision that my studies were junk science on the gasket studies. On the other hand, one of the more prestigious industrial hygiene journals in the world published it.

And as I've had to testify a number of times, the only thing I can think of is that I did a horrible job explaining

my work to that judge.

2.2

- Q. And, in fact, are you aware after that order where people sent that order to the editor of the journal that you were trying to publish your article?
- A. Yes, sir. After they'd gone through the peer-review process and accepted for publication, that Lamar County Order was actually sent to the editor to try to derail the publication.

So there has been some criticisms that maybe the peer-reviewers didn't know all the facts about our study.

The editor received the Lamar County hearing, and certainly the editor is the final reviewer. The editor just makes the decision if the paper goes forward or not, ultimately.

There was nothing in the -- there was nothing in the Lamar County hearing, excuse me, there was everything that the criticisms that have been leveled against our studies was in that hearing. So -- was in that order. So the editor always had the ability to pull the paper if he thought it was unscientific.

- Q. In fact, are you aware that Mr. Mangold, Mr. Liukonen folks who had testified on behalf of Garlock in asbestos litigation, had conversations or sent materials to the editor to try to keep this paper from being published?
- A. After it came out that the paper was accepted, it was

going to be published, Mr. Mangold wrote a letter to the editor, I think it was Larry Pearce, and sent along Lamar County hearing, actually suggesting they should pull the paper, even though they might be sued.

Α.

Yes, sir.

studies that you've done?

Larry Liukonen actually called the editor trying to get the publication stopped. I don't mean get the peer-reviewed process stopped. I mean get the fact that the paper had been accepted, and was ready to be published and get it stopped at that point.

- Q. Now Dr. Longo, anything about that entire process, and I guess after Lamar County, have you continued to testify across the country about these gasket studies? Has Mr. Hatfield, one of the individuals who works for you, has he testified in places like Los Angeles, California, Alameda, California and other places using these particular studies and this data set?
- Q. In fact, are you aware that experts from across the country rely on these things and testify, the peer-review
- A. Yes, sir. The gasket studies have been used many times, and these same studies, the paper, has been used many times in many courts across the country.
- Q. And since that time, Dr. Longo, have you, yourself, been in court and testified using the various studies that we used today?

- A. Yes, sir, I have.
- 2 0. Now -- in the State of Texas also?
- 3 A. Yes, sir.

1

10

11

- Q. Now, the last thing I want to talk to you about very briefly is, there's been some questions about whether asbestos actually adheres to gaskets. Because when Mr. Boelter was here, we showed some videos of his where the gasket came out
- and it was in one piece, and he and I had a discussion about what was intact or not.
  - Would you say if asbestos -- if a gasket comes out and it's one entire piece, would that be intact?
- 12 A. I would call that intact.
- 13 0. Okay.
- 14 A. But I need to -- it's -- it's not the asbestos that
  15 sticks to the gasket. I just need to -- I'm sorry, I don't
- 16 mean to correct you.
- 17 Q. No. No. You're the expert, not me.
- 18 THE COURT: You meant the gasket to the flange?
- 19 THE WITNESS: Right.
- 20 MR. FROST: Right.
- 21 THE WITNESS: It's not the asbestos that causes it
- 22 to stick. It's actually the synthetic rubber which is a
- 23 viscoelastic material that flows down into the cracks and
- 24 crevices and then adheres over time because the chemistry
- 25 change. That's what's causing the --

BY MR. FROST:

Q. Is there anything in regards to the tools that the pipefitter used -- there was some discussion that maybe you guys were jamming them in and those flanges were very sensitive and you were causing ripples in it. Anything about those tools that caused any of that that you're aware of?

A. A solid steel flange beats a putty knife. No. Again, this was a pipefitter doing this work. And to me, you can't have it both ways.

Either these gaskets can release asbestos fibers, depending on the work activity you're doing or they can't. You know, there's no middle ground here.

So if the activity being suggested is too rough, too aggressive, and that's why we got our fiber levels. Well hence, that means gaskets can release significant fibers.

Then you have to look at the work activities of the workers. If it's the fact that these gaskets are encapsulated and cannot release fibers, then it wouldn't matter what work activity you do to it. The work activities that we're doing is what the pipefitters did, is what I read in depositions, what I hear when I talk to folks about these are common techniques.

It's -- I don't believe, it's not my opinion, that these activities are causing all this severe damage to the flange. You got to remember, what they're trying to do when they have

- the putty knife, and they're trying to get up under, break
  through the gasket and get up under to try to lift as much off
- 3 of the gasket as they can.
- Q. And Dr. Longo, are you aware that Garlock is also aware of the fact that they even developed some gaskets that had
- 6 antistick coating to try to deal with this exact issue?
- 7 A. Yes, sir. I think this is some of the best evidence that
- 8 asbestos -- that gaskets stick to flanges and is a problem.
- 9 Or if it didn't, why would a company who sells gaskets spend
- 10 | time and research and effort back in 2009 to develop a gasket
- 11 | that will not stick to a flange?
- 12 Q. And in fact, have they done videos where they describe
- 13 | the types of materials that they're trying to develop to try
- 14 to keep gaskets from sticking to flanges?
- 15 A. Yes, sir.
- 16 Q. And you've reviewed those?
- 17 A. I have.
- 18 Q. Okay.
- 19 (Video plays.)
- 20 Q. So Dr. Longo, the first parts that we saw there were not
- 21 | using this new technology, but using the older technology, not
- 22 | the antistick, correct?
- 23 A. Yes, sir, that's correct.
- 24 | Q. And what's important about what we've just seen in
- 25 regards to your studies and how they relate to whether they

are replicable or whether the techniques you guys used or what was being used in industry?

A. I think most importantly here it shows that a gasket being put into a test flange and brought to a temperature of 400 degrees Fahrenheit for only 24 hours, stuck and hardened the gasket.

Notice the comment there that the gasket was harder than the brass chisel, and they had to use the same techniques that we used in order to get the gaskets off our flanges where you had to get a carbon steel putty knife. They're using the blade portion of it, and hitting it with a hammer.

If a gasket can stick to that degree in 24 hours at 400 degrees Fahrenheit, think about in a steam system where these gaskets can be in there from months to years. So the suggestion that they don't really stick is just not -- is just not feasible. Of course they stick, it's the main problem.

If you read their literature, they talk about the viscoelastic properties of gasket. And what visco -- viscus and elastic, it flows. It flows into the crevices and over -- in that elevated temperature and pressure it adheres, Garlock says it happens.

So the finding of our studies where the gaskets, these synthetic rubber chrysotile gaskets stick, is not something that I made up. It is something that pipefitters and steamfitters talk about repeatedly, that the problem of

1 removing these gaskets.

And I think this was 2009 that this came out, I interpret that as Garlock has done the research to figure out how to make gaskets for these extreme conditions, elevated temperature and pressure not stick.

So if they're doing this in 2009, how can they say this did not happen in the '50s, the '60s, the '70s and the '80s?

MR. FROST: And Dr. Longo, we have marked as ACC Exhibit 3645 your CV.

Your Honor, we would offer that into evidence at this time.

MR. HARRIS: No objection, Your Honor.

MR. FROST: And, Your Honor, we would offer for demonstrative purposes and for Rule 104 purposes, Dr. Longo's expert report and exhibits, which is ACC 3646; Dr. Longo's expert rebuttal report and exhibits, which is ACC 3647. We would also offer the PowerPoint for demonstrative and Rule 104 purposes as ACC 3649, and the videotapes and other demonstratives including the videos we just showed as ACC 3785 for demonstrative and Rule 104 purposes.

MR. HARRIS: No objection, Your Honor.

THE COURT: We will admit those.

(ACC's Exhibits No. 3645, 3636, 3647, 3649, 3685 were received into evidence.)

MR. FROST: And Your Honor, pass the witness.

THE COURT: Want to break for lunch now? It's a 1 2 good time. Just come back at quarter to 2:00. Will that give 3 you enough time? 4 MR. HARRIS: Yes, Your Honor. 5 (Lunch recess at 12:40 p.m.) 6 UNITED STATES DISTRICT COURT 7 WESTERN DISTRICT OF NORTH CAROLINA CERTIFICATE OF REPORTER 8 9 I, Laura Andersen, Official Court Reporter, certify that the foregoing transcript is a true and correct transcript of the proceedings taken and transcribed by me to the best of 10 my ability. 11 Dated this the 29th day of July, 2013. 12 13 s/Laura Andersen 14 Laura Andersen, RMR Official Court Reporter 15 16 17 18 19 20 21 2.2 23 24 25 Laura Andersen, RMR 704-350-7493